



# G-Box Expert ATF DX III

## Description

Multigrade hydraulic fluid G-Box ATF DX III delivers high performance properties and operating stability. The product is designed for use in automatic gearboxes, transmissions and steering boosters of cars, trucks, buses and off-rovers, as well as construction and specialty vehicles where DEXRON IIIG fluid type is required.

## Benefits

- Optimum friction properties ensure vibration-free smooth gearshift
- High thermal and oxidation resistance maintains initial performance level throughout the lubricants life
- Good pumping ability at low temperatures
- Anti-wear and anti-corrosion properties prolong transmission life
- Compatible with seal materials

## Applications

- Fixed-ratio automatic transmission mechanisms requiring the use of Dexron IIIG, IID
- Steering boosters where ATF fluids are recommended

## Specifications and Approvals

**G-Box Expert ATF DX III meets the requirements of:**

- DEXRON IIIG
- Ford MERCON
- ZF TE-ML 02F, 03D, 04D, 05L, 09, 11B, 14A, 17C, 21L
- Voith H55.6335
- MAN 339 V1/Z1
- MB 236.1, 236.2, 236.3, 236.5, 236.6, 236.7, 236.11
- Volvo CE 97340, 97341
- Allison C-4
- GM TASA
- Cat TO-2

## Typical Properties

### G-Box Expert ATF DX III

Viscosity,		
• cSt @ 100°C	GOST 33	7.3
Brookfield Viscosity @ -40°C	ASTM D 2983	18000
Flash Point, COC, °C	GOST 4333	217
Pour Point, °C	GOST 20287	-48
Density, kg/m <sup>3</sup> @ 15°C	GOST 3900	860

## Health and Safety

When used as directed, G-Box ATF DX III has no adverse effects either on health or environment. Beyond normal hygiene no special precautions are required. Avoid contact with skin. Use protective gloves. In case of contact flush immediately with water and soap. For more information please refer to the Safety Data Sheet.

## Reduced Environmental Impact

Place used product in an appropriate waste disposal container. Dispose via a licensed waste disposal contractor. Do not discharge waste lubricant into groundwater, watercourses, soil, sewerage or drainage systems.

