

## G-Box ATF DX II

Automatic Transmission Fluid



Mineral base oils



Automatic transmission



Power steering



Excellent frictional properties



Low-temperature performance



Anti-wear protection

**G-Box ATF DX II** is high performance automatic transmission fluid recommended for older passenger car and commercial automatic transmissions. It is specifically engineered to provide smooth and controlled friction and wear characteristics. G-Box ATF DX II can be used in power steering systems and hydraulic applications where automatic transmission fluid is specified.

### Applications



- Passenger and commercial automatic transmissions specifying DEXRON® IID level performance
- Power steering systems and hydraulic applications where automatic transmission fluid is specified
- Some manual transmissions where automatic transmission fluid is specified

Features	Advantages and Potential Benefits
Good thermal and oxidation stability	Reduced deposits and sludge build-up to keep transmissions clean for efficient operation
Good low temperature performance	Good fluidity at low temperatures providing good cold-start shifting
Good anti-wear properties	Reduced wear and extended life in transmissions
Compatible with all common seal materials	Excellent leakage control

#### Meets the requirements:

- Allison C-4
- Ford MERCON
- General Motors DEXRON® IID
- ZF TE-ML 02F, 09, 11


#### Approvals:

- MAN 339 Type L2
- MAN 339 Type V1/Z1
- MB 236.1
- Voith H55.6335
- ZF TE-ML 03D, 04D, 14A, 17C

### Typical Characteristics

Properties	Method	G-Box ATF DX II
Color	visually	red
Kinematic Viscosity@40°C, mm <sup>2</sup> /s	ASTM D445	38,8
Kinematic Viscosity@100°C, mm <sup>2</sup> /s	ASTM D445	7,6
Viscosity Index	ASTM D2270	168
Flash Point (COC), °C	ASTM D92	205
Pour Point, °C	ASTM D97	-45
Density @15°C, kg/m <sup>3</sup>	ASTM D4052	872

## G-Box ATF DX II performance benefits




**Gears and bearings protection:**  
Excellent wear protection at high temperatures – scuffing load-carrying capacity 9% higher (DIN 51354 A/8,3/90)

**Smooth shifting performance:**  
Stable viscosity during drain interval – viscosity loss 7% lower (DIN 51350-6 KRL/C)


Low temperature Brookfield apparent viscosity 1.6 times lower (DIN 51398)

**Leakage control:**  
Effect on vulcanized and thermoplastic rubbers 3.3 times lower (DIN ISO 1817)

Effect on rubbers\*



Wear protection\*\*



\*DIN ISO 1817; \*\*DIN 51354 A/8,3/90

## Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.

ISO 9001

ISO 14001

ISO/TS 16949

OHSAS 18001

CERTIFIED

GAZPROMNEFT – LUBRICANTS, LTD.  
14/3, Krzhyzhanovskogo Street, Moscow, 117218 Russia  
Tel: +7 (495) 642-99-69  
Fax: +7 (495) 921-48-63  
[www.gazpromneft-oil.com](http://www.gazpromneft-oil.com)

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. The information contained is subject to change without notice. Gazpromneft-Lubricants accept no liability for any damage or loss resulting from using the product in purposes other than it intended, from any failure to comply with the recommendations or from hazards inherent in the nature of the material. If you require any further information please consult our technical helpdesk. E-mail: [OilSupport@gazprom-neft.ru](mailto:OilSupport@gazprom-neft.ru) 05/2018