



Gazpromneft Premium GF-5 5W-30 ***Synthetic energy saving engine oil***

DESCRIPTION

Synthetic energy saving engine oil for using in gasoline engines (with/without turbocharge), installed at passenger cars, vans, minibuses and light trucks of Japanese, Korean, Chinese and American production.

BENEFITS

- Exhibits energy saving properties and provides fuel economy due to specially selected combination of base oils and additives including the latest friction modifiers
- Ensures engine cleanness and prevents deposit, sludge and lacquer formation, which is proved by tests for meeting ILSAC GF-5 requirements for piston cleanness.
- Provides turbine cleanness and prevents it from deposits
- Superior anti-oxidation properties ensure prolonged service life
- Compatible with seal materials (such as polyacrylate rubber, nitrile rubber, silicone rubber, fluorocarbon rubber and ethylene acrylic rubber)
- Ensures prolonged oil drain interval and provides effective lubrication

APPLICATION

- Intended for use in cars, produced by Toyota, Lexus, Subaru, Mazda, Suzuki, Mitsubishi, Honda, Hyundai, Kia and other vehicles requiring oils that meet ILSAC GF-3, 4, 5 specifications
- Also applicable for gasoline engines of cars, vans, minibuses and light trucks of Japanese, Korean, Chinese and American production, where it is recommended to use oils meeting requirements API SN (or earlier specifications) or ILSAC GF-3, 4, 5, with viscosity SAE 5W-30

SPECIFICATIONS AND APPROVALS

Gazpromneft Premium GF-5 5W-30 is meeting requirements of the following specifications:

- API SN
- ILSAC GF-5



PHYSICAL AND TECHNICAL CHARACTERISTICS

<i>TYPICAL PROPERTIES</i>	<i>Gazpromneft Premium GF-5 5W-30</i>
Kinematic viscosity @ 100 °C, mm ² /s	11,2
Flash point, COC, °C	232
Pour point, °C	-44
Density, @ 20 °C, g/cm ³	849,1
Base number, mg KOH/g, ADTM D2896	7,5
Sulfated ash, %	0,9

HEALTH AND SAFETY

When used as directed, Gazpromneft Premium GF-5 5W-30 oil has no adverse effects either on health or environment. Beyond normal hygiene no special precautions are required. Avoid contact with skin. Use protective gloves. In case of contact flush immediately with water and soap. For more information please refer to the Safety Data Sheet.

ENVIRONMENTAL PROTECTION

Place used product in an appropriate waste disposal container. Dispose via a licensed waste disposal contractor. Do not discharge waste lubricant into groundwater, watercourses, soil, sewerage or drainage systems.