



## **Gazpromneft Premium L**

**5W-40, 5W-30, 10W-40, 10W-30, 15W-40, 20W-50**  
**All purpose multigrade engine oils**

### **PRODUCT DESCRIPTION**

Motor oils Gazpromneft Premium L 5W-40, 5W-30, 10W-30, 10W-40 are semi-synthetic and Gazpromneft Premium L 15W-40, 20W-50 is mineral produced using high quality base oils and a balanced set of additives. Due to the use of improved base oils the motor oils possess the following features: extended service life, reduced oil consumption through burning and improved anticorrosion properties.

### **ADVANTAGES**

- Due to the effective combination of high-quality base oils and additives provides reliable protection of the engine against wear out both during the cold start-up and in different operating conditions.
- High detergent-dispersant properties of oils provide increased motor cleanliness, resistance to formation of all types of deposits.
- Meet requirements API SL/CF, including requirements for oil consumption, evaporation, deposits and cleanliness of the cylinder-piston group.
- Provides reliable motor protection at high ambient temperatures (20W-50).

### **APPLICATION**

Suitable use in gasoline and diesel engines of the passengers cars, light trucks and vans (with or without turbocharging), where the lubricants of operating class API SL/CF (or earlier specifications) and the corresponding viscosity grade are recommended: SAE 5W-40/SAE 5W-30/SAE 10W-40/SAE 10W-30/SAE 15W-40/SAE 20W-50.

### **SPECIFICATIONS AND APPROVALS**

**Gazpromneft Premium L 5W-40, 5W-30, 10W-40, 10W-30, 15W-40, 20W-50 oils are approved/comply with the following specifications requirements:**

- API SL/CF
- ACEA A3/B4 (Gazpromneft Premium L 10W-40 only)
- ACEA A3/B3 (Gazpromneft Premium L 5W-40, 5W-30, 10W-40, 15W-40, 20W-50 only)
- MB 229.1 (Gazpromneft Premium L 10W-40 only)
- JSC "AVTOVAZ" (Gazpromneft Premium L 5W-40, 5W-30, 10W-40, 20W-50 only)
- Certified by AAI (Gazpromneft Premium L 5W-40, 5W-30, 10W-40, 20W-50 only)



## PHYSICAL AND TECHNICAL CHARACTERISTICS

<b>TYPICAL PROPERTIES Gazpromneft Premium L</b>	<b>5W-40</b>	<b>5W-30</b>	<b>10W-40</b>	<b>10W-30</b>	<b>15W-40</b>	<b>20W-50</b>
Viscosity, cSt @ 100 °C	14,5	11,7	14,4	12,1	14,8	18,9
Viscosity, cSt @ 40 °C	89,1	72,6	98,3	81,33	114,5	178,2
Viscosity Index	170	156	151	129	133	120
Flash Point, COC, °C	232	230	229	234	236	240
Pour Point, °C	-38	-38	-36	-36	-30	-29
Base Number, mg KOH/g	9,0	9,0	9,0	9,0	9,0	9,0
Density @ 20 °C, g/sm <sup>3</sup>	0,856	0,863	0,873	0,870	0,881	0,889
Sulphated Ash, %	1,3	1,3	1,3	1,3	1,3	1,3

## HEALTH AND SAFETY

Subject to the rules of personal and industrial hygiene, as well as proper use in the recommended application fields, the Gazpromneft Premium L 5W-40, 5W-30, 10W-30, 10W-40, 15W-40, 20W-50 oils do not constitute any threat to the health and environment. Avoid oil contact with skin. When changing oil use protective gloves. In case of oil contact with skin, immediately rinse it with water and soap. See the detailed information concerning health and safety in the product safety data sheet.

## ENVIRONMENTAL PROTECTION

Scavenge oil and residual products should be collected in a sealed container and handed over to the scavenge oil collection stations. Do not drain scavenge oil to the sewage facilities, ground or impoundments.