

Gazpromneft Premium L 5W-30

Passenger Vehicle Engine Oils



Engine oil



Semisynthetic



Engine cleanliness



Gasoline and diesel engines



Multigrade



Advanced polymers

Gazpromneft Premium L 5W-30 is high quality semi-synthetic engine oil providing excellent high temperature wear protection, cold start performance and inhibits deposit formation. It is formulated with the use of synthetic technology and advanced additive system to provide improved performance level compared with conventional oils. Gazpromneft Premium L 5W-30 provides long engine life for many types and ages of vehicles with enhanced protection over a wide temperature range.

Applications



- Turbo-charged and direct injection high performance engines
- Gasoline and diesel engines without diesel particulate filters (DPF) requiring oil with ACEA A3/B3 or API SL, API CF standards
- Passenger cars, SUV's, light trucks and vans

Features	Advantages and Potential Benefits
Multi-purpose application	High quality formulation suitable for a wide range of vehicles requiring premium quality product
Excellent low temperature performance	Quick cold weather starting helps to extend engine life
Wear protection	Strong oil film provides protection against wear under all operating conditions for long engine life
Improved thermal and oxidation stability	Helps to resist oil aging allowing extended drain interval protection
Deposit control	Prevents forming of sludge and harmful deposits through the use of advanced detergent additives for engine cleanliness
Stay-in-grade	Keeps protective oil film during the whole drain interval and maintains viscosity grade

Meet the requirements:

- ACEA A3/B3
- API SL
- API CF
- AVTOVAZ

Typical Characteristics

Properties	Method	Gazpromneft Premium L 5W-30
SAE Viscosity Grade	SAE J300	5W-30
Kinematic Viscosity @40°C, mm ² /s	ASTM D445	72,6
Kinematic Viscosity @100°C, mm ² /s	ASTM D445	11,7
Viscosity Index	ASTM D2270	156
Flash Point (COC), °C	ASTM D92	230
Pour Point, °C	ASTM D97	-45
Total Base Number, mg KOH/g	IP 3016	9,0
Density @15°C, kg/m ³	ASTM D4052	863
Sulfated Ash, wt%	ASTM D874	1,3

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.

Gazpromneft Premium L 5W-30 recommendations*

Makes	Models	Engines
CHEVROLET	AVEO, CAPTIVA, LANOS, NIVA, REZZO, VIVA	Gasoline and Diesel before 2006
DACIA	SUPERNOVA, SOLENZA, SANDERO, LOGAN, DUSTER, LODGYM DOKKER	Gasoline before 2004
DAEWOO	MATIZ, NEXIA, GENTRA	Gasoline
DAIHATSU	CUORE, MIRA, CHARADE, TREVIS, MOVE, SIRION, YOUNG RV MATERIA, TERIOS, COPEN	Gasoline
DATSUN	MI-DO, ON-DO	Gasoline
FIAT	500, DOBLO, 600, SEICENTO, PANDA, PALIO, ALBEA, SIENA, IDEA, PUNTO, LINEA, BARCETTA, BRAVO, STILO, MAREA, CROMA, SEDICI, MULTIPLA	Gasoline and Diesel without particulate filters before 2010
GAZ	3102, 31029, 3110, SIBER	Gasoline
GEELY	BEAUTY LEOPARD, BORUI, FREE CRUISER, EMGRAND, YUANJIN, VISION, GL EAGLE, HOAQING, LC PANDA, MEIRI ULIOU, KING KONG, JINGYING	Gasoline before 2014
GREAT WALL	FLORID, VOLEEX, COOLBEAR, HAVAL, HOVER	Gasoline before 2011
HAIMA	2, 7, FAMILY, FREEMA, M, S	Gasoline
HONDA	JAZZ, CIVIC, STREAM, ACCORD, LEGEND, HR-V, CR-V, NSX	Gasoline before 2004 and Diesel without particulate filters before 2005
HYUNDAI	ACCENT, GETZ, MATRIX, SANTA FE, SONATA, TERRACAN, TUCSON	Gasoline and Diesel before 2008
KIA	CARENS, CARNAVAL, CERATO, MAGENTIS/OPTIMA, PICANTO, SORENTO, SPECTRA/SEPHIA/SHUMA, SPORTAGE	Gasoline and Diesel before 2008
LADA	All models	Gasoline
LIFAN	320, 520, 620, 720	Gasoline
MAZDA	2,3, 323, 6, ATENZA, CAPELLA, DEMIO, FAMILIA, PREMACY	Gasoline and Diesel before 2004
MITSUBISHI	AIRTREK, CARISMA, COLT, GALANT, GRANDIS, L200, LANCER, CEDIA, LIBERO, MIRAGE, OUTLANDER, PAJERO, PININ, SPORT, SPACE STAR	Gasoline and Diesel before 2009
NISSAN	ALMERA, CUBE, EVALIA, JUKE, LEAF, MAXIMA QX, MICRA, MARCH, MURANO, NAVARA, NOTE, PATHFINDER, PATROL, TER ANO, PIXA, PULSAR, PRIMERA, QASHQAI, SKYLINE, TEANA, TIIDA, X-TRAIL	Gasoline and Diesel without particulate filters
RENAULT (RUS)	CLIO, DUSTER, FLUENCE, LAGUNA, LOGAN, MEGANE, SANDERO, SCENIC, SYMBOL	Gasoline and Diesel without particulate filters
SUBARU	IMPREZA, FORESTER, LEGACY	Gasoline before 2005
SUZUKI	ALTO, CELERIO, WAGON, SPLASH, SWIFT, IGNIS, SX4, LIANA, KIZASHI, JIMNY, VITARA, GRAND VITARA	Gasoline before 2005
TAGAZ	VEGA, TAGER	Gasoline
TOYOTA	AVENSIS, CALDINA, CAMRY, CARINA, COROLLA, CORONA, GAIA, HARRIER, HIGHLANDER, HILUX, IPSUM, IST, LAND CRUISER, MARK, NADIA, NOAH, OPA, PLATZ, PREMIO, PRIUS, RAV 4, SUCCEED, VERSO, VISTA, VITZ, WISH, YARIS	Diesel without particulate filters before 2007
UAZ	3151, HUNTER, PATRIOT, PICKUP, CARGO	Gasoline and Diesel

* Third party data is used to determine the recommended products. Gazpromneft Lubricants accepts no liability for the suitability of any recommendation made. Any decisions you make based on this information are your sole responsibility. Before adding any products to your vehicle, please always check vehicle/equipment handbook to confirm the suitability of any product recommendations for your vehicle/equipment.

Gazpromneft Premium L 5W-40

Passenger Vehicle Engine Oils



Engine oil



Semisynthetic



Engine cleanliness



Gasoline and diesel engines



Multigrade



Advanced polymers

Gazpromneft Premium L 5W-40 is high quality semi-synthetic engine oil providing excellent high temperature wear protection, cold start performance and inhibits deposit formation. It is formulated with the use of synthetic technology and advanced additive system to provide improved performance level compared with conventional oils. Gazpromneft Premium L 5W-40 provides long engine life for many types and ages of vehicles with enhanced protection over a wide temperature range.

Applications



- Turbo-charged and direct injection high performance engines
- Gasoline and diesel engines without diesel particulate filters (DPF) requiring oil with ACEA A3/B3 or API SL, API CF standards
- Passenger cars, SUV's, light trucks and vans

Features	Advantages and Potential Benefits
Multi-purpose application	High quality formulation suitable for a wide range of vehicles requiring premium quality product
Excellent low temperature performance	Quick cold weather starting helps to extend engine life
Wear protection	Strong oil film provides protection against wear under all operating conditions for long engine life
Improved thermal and oxidation stability	Helps to resist oil aging allowing extended drain interval protection
Deposit control	Prevents forming of sludge and harmful deposits through the use of advanced detergent additives for engine cleanliness
Stay-in-grade	Keeps protective oil film during the whole drain interval and maintains viscosity grade

Meet the requirements:

- ACEA A3/B3
- API SL
- API CF
- AVTOVAZ

Typical Characteristics

Properties	Method	Gazpromneft Premium L 5W-40
SAE Viscosity Grade	SAE J300	5W-40
Kinematic Viscosity @40°C, mm ² /s	ASTM D445	89,1
Kinematic Viscosity @100°C, mm ² /s	ASTM D445	14,5
Viscosity Index	ASTM D2270	170
Flash Point (COC), °C	ASTM D92	232
Pour Point, °C	ASTM D97	-45
Total Base Number, mg KOH/g	IP 3016	9,0
Density @15°C, kg/m ³	ASTM D4052	856
Sulfated Ash, wt%	ASTM D874	1,3

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.

Gazpromneft Premium L 5W-40 recommendations*

Makes	Models	Engines
CHERY	QQ6, CHANCE, M, TENGO, A, INDIS, E5, ARRIZO, RIICH, J11, TIGGO, BOSS, CROSSEASTAR	Gasoline
CHEVROLET	AVEO, CAPTIVA, LANOS, NIVA, REZZO, VIVA	Gasoline and Diesel before 2006
DACIA	SUPERNOVA, SOLENZA, SANDERO, LOGAN, DUSTER, LODGYM DOKKER	Gasoline before 2004
DAEWOO	MATIZ, NEXIA, GENTRA	Gasoline
DAIHATSU	CUORE, MIRA, CHARADE, TREVIS, MOVE, SIRION, YOUNG RV, MATERIA, TERIOS, COPEN	Gasoline
DATSUN	MI-DO, ON-DO	Gasoline
FIAT	500, DOBLO, 600, SEICENTO, PANDA, PALIO, ALBEA, SIENA, IDEA, PUNTO, LINEA, BARCHETTA, BRAVO, STILO, MAREA, CROMA, SEDICI, MULTIPLA	Gasoline and Diesel without particulate filters before 2010
GAZ	3102, 31029, 3110, SIBER	Gasoline
GEELY	BEAUTY LEOPARD, BORUI, FREE CRUISER, EMGRAND, YUANJIN, VISION, GL EAGLE, HOAQING, LC PANDA, MEIRI ULIOU, KING KONG, JINGYING	Gasoline before 2014
GREAT WALL	FLORID, VOLEEX, COOLBEAR, HAVAL, HOVER	Gasoline before 2011
HONDA	JAZZ, CIVIC, STREAM, ACCORD, LEGEND, HR-V, CR-V, NSX	Gasoline before 2004
HYUNDAI	ACCENT, GETZ, MATRIX, SANTA FE, SONATA, TERRACAN, TUCSON	Gasoline and Diesel before 2008
KIA	CARENS, CARNAVAL, CERATO, MAGENTIS/OPTIMA, PICANTO, SORENTO, SPECTRA/SEPHIA/SHUMA, SPORTAGE	Gasoline and Diesel before 2008
LADA	All models	Gasoline
LIFAN	320, 520, 620, 720	Gasoline
MAZDA	2,3, 323, 6, ATENZA, CAPELLA, DEMIO, FAMILIA, PREMACY	Gasoline Diesel before 2004
MITSUBISHI	AIRTREK, CARISMA, COLT, GALANT, GRANDIS, L200, LANCER, CEDIA, LIBERO, MIRAGE, OUTLANDER, PAJERO, PININ, SPORT, SPACE STAR	Gasoline and Diesel before 2009
NISSAN	ALMERA, CUBE, EVALIA, JUKE, LEAF, MAXIMA QX, MICRA, MARCH, MURANO, NAVARA, NOTE, PATHFINDER, PATROL, TERRANO, PIXA, PULSAR, PRIMERA, QASHQAI, SKYLINE, TEANA, TIIDA, X-TRAIL	Gasoline and Diesel without particulate filters
RENAULT (RUS)	CLIO, DUSTER, FLUENCE, LAGUNA, LOGAN, MEGANE, SANDERO, SCENIC, SYMBOL	Gasoline
SUZUKI	ALTO, CELERIO, WAGON, SPLASH, SWIFT, IGNIS, SX4, LIANA, KIZASHI, JIMNY, VITARA, GRAND VITARA	Gasoline and Diesel without particulate filters before 2005
TAGAZ	VEGA, TAGER	Gasoline
TOYOTA	AVENSIS, CALDINA, CAMRY, CARINA, COROLLA, CORONA, GAIA, HARRIER, HIGHLANDER, HILUX, IPSUM, IST, LAND CRUISER, MARK, NADIA, NOAH, OPA, PLATZ, PREMIO, PRIUS, RAV 4, SUCCEED, VERSO, VISTA, VITZ, WISH, YARIS	Diesel without particulate filters before 2007
UAZ	3151, HUNTER, PATRIOT, PICKUP, CARGO	Gasoline and Diesel
CHERY	QQ6, CHANCE, M, TENGO, A, INDIS, E5, ARRIZO, RIICH, J11, TIGGO, BOSS, CROSSEASTAR	Gasoline

* Third party data is used to determine the recommended products. Gazpromneft Lubricants accepts no liability for the suitability of any recommendation made. Any decisions you make based on this information are your sole responsibility. Before adding any products to your vehicle, please always check vehicle/equipment handbook to confirm the suitability of any product recommendations for your vehicle/equipment.



Gazpromneft Premium L 10W-30

Passenger Vehicle Engine Oils



Engine oil



Semisynthetic



Engine cleanliness



Gasoline and diesel engines



Multigrade



Advanced polymers

Gazpromneft Premium L 10W-30 is high quality semi-synthetic engine oil providing excellent high temperature wear protection, cold start performance and inhibits deposit formation. Gazpromneft Premium L 10W-30 is formulated with the use of synthetic technology and advanced additive system to provide improved performance level compared with conventional oils. It provides long engine life for many types and ages of vehicles with enhanced protection over a wide temperature range.

Applications



- Turbo-charged and direct injection high performance engines
- Gasoline and diesel engines without diesel particulate filters (DPF) requiring oil with API SL/CF standard
- Passenger cars, SUV's, light trucks and vans

Features	Advantages and Potential Benefits
Broad vehicle application	High quality formulation suitable for a wide range of vehicles requiring premium quality product
Excellent low temperature performance	Quick cold weather starting helps to extend engine life
Wear protection	Strong oil film provides protection against wear under all operating conditions for long engine life
Improved thermal and oxidation stability	Helps to resist oil aging allowing extended drain interval protection
Deposit control	Prevents forming of sludge and harmful deposits through the use of advanced detergent additives for engine cleanliness
Stay-in-grade	Keeps protective oil film during the whole drain interval and maintains viscosity grade

Meet the requirements:

- API SL/CF

Typical Characteristics

Properties	Method	Gazpromneft Premium L 10W-30
SAE Viscosity Grade	SAE J300	10W-30
Kinematic Viscosity @40°C, mm ² /s	ASTM D445	81,3
Kinematic Viscosity @100°C, mm ² /s	ASTM D445	12,1
Viscosity Index	ASTM D2270	129
Flash Point (COC), °C	ASTM D92	234
Pour Point, °C	ASTM D97	-36
Total Base Number, mg KOH/g	IP 3016	9,0
Density @15°C, kg/m ³	ASTM D4052	870
Sulfated Ash, wt%	ASTM D874	1,3

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.

Gazpromneft Premium L 10W-30 recommendations*

Makes	Models	Engines
CHEVROLET	AVEO, CAPTIVA, LANOS, NIVA, REZZO, VIVA	Gasoline and Diesel before 2006
DACIA	SUPERNOVA, SOLENZA, SANDERO, LOGAN, DUSTER, LODGYM DOKKER	Gasoline before 2004
DAEWOO	MATIZ, NEXIA, GENTRA	Gasoline
DAIHATSU	CUORE, MIRA, CHARADE, TREVIS, MOVE, SIRION, YOUNG RV MATERIA, TERIOS, COPEN	Gasoline
DATSUN	MI-DO, ON-DO	Gasoline
FIAT	500, DOBLO, 600, SEICENTO, PANDA, PALIO, ALBEA, SIENA, IDEA, PUNTO, LINEA, BARCETTA, BRAVO, STILO, MAREA, CROMA, SEDICI, MULTIPLA	Gasoline and Diesel without particulate filters before 2010
GAZ	3102, 31029, 3110, SIBER	Gasoline
GEELY	BEAUTY LEOPARD, BORUI, FREE CRUISER, EMGRAND, YUANJIN, VISION, GL EAGLE, HOAQING, LC PANDA, MEIRI ULIOU, KING KONG, JINGYING	Gasoline before 2014
GREAT WALL	FLORID, VOLEEX, COOLBEAR, HAVAL, HOVER	Gasoline before 2011
HAIMA	2, 7, FAMILY, FREEMA, M, S	Gasoline
HONDA	JAZZ, CIVIC, STREAM, ACCORD, LEGEND, HR-V, CR-V, NSX	Gasoline before 2004 and Diesel without particulate filters before 2005
HYUNDAI	ACCENT, GETZ, MATRIX, SANTA FE, SONATA, TERRACAN, TUCSON	Gasoline and Diesel before 2008
KIA	CARENS, CARNAVAL, CERATO, MAGENTIS/OPTIMA, PICANTO, SORENTO, SPECTRA/SEPHIA/SHUMA, SPORTAGE	Gasoline and Diesel before 2008
LADA	All models	Gasoline
LIFAN	320, 520, 620, 720	Gasoline
MAZDA	2,3, 323, 6, ATENZA, CAPELLA, DEMIO, FAMILIA, PREMACY	Gasoline and Diesel before 2004
MITSUBISHI	AIRTREK, CARISMA, COLT, GALANT, GRANDIS, L200, LANCER, CEDIA, LIBERO, MIRAGE, OUTLANDER, PAJERO, PININ, SPORT, SPACE STAR	Gasoline and Diesel before 2009
NISSAN	ALMERA, CUBE, EVALIA, JUKE, LEAF, MAXIMA QX, MICRA, MARCH, MURANO, NAVARA, NOTE, PATHFINDER, PATROL, TER ANO, PIXA, PULSAR, PRIMERA, QASHQAI, SKYLINE, TEANA, TIIDA, X-TRAIL	Gasoline and Diesel without particulate filters
RENAULT (RUS)	CLIO, DUSTER, FLUENCE, LAGUNA, LOGAN, MEGANE, SANDERO, SCENIC, SYMBOL	Gasoline and Diesel without particulate filters
SUBARU	IMPREZA, FORESTER, LEGACY	Gasoline before 2005
SUZUKI	ALTO, CELERIO, WAGON, SPLASH, SWIFT, IGNIS, SX4, LIANA, KIZASHI, JIMNY, VITARA, GRAND VITARA	Gasoline before 2005
TAGAZ	VEGA, TAGER	Gasoline
TOYOTA	AVENSIS, CALDINA, CAMRY, CARINA, COROLLA, CORONA, GAIA, HARRIER, HIGHLANDER, HILUX, IPSUM, IST, LAND CRUISER, MARK, NADIA, NOAH, OPA, PLATZ, PREMIO, PRIUS, RAV 4, SUCCEED, VERSO, VISTA, VITZ, WISH, YARIS	Diesel without particulate filters before 2007
UAZ	3151, HUNTER, PATRIOT, PICKUP, CARGO	Gasoline and Diesel

* Third party data is used to determine the recommended products. Gazpromneft Lubricants accepts no liability for the suitability of any recommendation made. Any decisions you make based on this information are your sole responsibility. Before adding any products to your vehicle, please always check vehicle/equipment handbook to confirm the suitability of any product recommendations for your vehicle/equipment.

Gazpromneft Premium L 10W-40

Passenger Vehicle Engine Oils



Engine oil



Semisynthetic



Engine cleanliness



Gasoline and diesel engines



Multigrade



Advanced polymers

Gazpromneft Premium L 10W-40 is high quality semi-synthetic engine oil providing excellent high temperature wear protection, cold start performance and inhibits deposit formation. Gazpromneft Premium L 10W-40 is formulated with the use of synthetic technology and advanced additive system to provide improved performance level compared with conventional oils. It provides long engine life for many types and ages of vehicles with enhanced protection over a wide temperature range.

Applications



- Turbo-charged and direct injection high performance engines
- Gasoline and diesel engines without diesel particulate filters (DPF) requiring oil with ACEA A3/B4 or API SL, API CF standards
- Passenger cars, SUV's, light trucks and vans

Features	Advantages and Potential Benefits
Broad vehicle application	High quality formulation suitable for a wide range of vehicles requiring premium quality product
Excellent low temperature performance	Quick cold weather starting helps to extend engine life
Wear protection	Strong oil film provides protection against wear under all operating conditions for long engine life
Improved thermal and oxidation stability	Helps to resist oil aging allowing extended drain interval protection
Deposit control	Prevents forming of sludge and harmful deposits through the use of advanced detergent additives for engine cleanliness
Stay-in-grade	Keeps protective oil film during the whole drain interval and maintains viscosity grade

Meet the requirements:

- ACEA A3/B4
- API SL (licensed)
- API CF
- MB 229.1

Approvals:

- AVTOVAZ
- UMZ-GAZ

Typical Characteristics

Properties	Method	Gazpromneft Premium L 10W-40
SAE Viscosity Grade	SAE J300	10W-40
Kinematic Viscosity @40°C, mm ² /s	ASTM D445	98,3
Kinematic Viscosity @100°C, mm ² /s	ASTM D445	14,4
Viscosity Index	ASTM D2270	151
Flash Point (COC), °C	ASTM D92	229
Pour Point, °C	ASTM D97	-39
Total Base Number, mg KOH/g	IP 3016	9,0
Density @15°C, kg/m ³	ASTM D4052	873
Sulfated Ash, wt%	ASTM D874	1,3

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.

Gazpromneft Premium L 10W-40 recommendations*

Makes	Models	Engines
CHERY	QQ6, CHANCE, M, TENGO, A, INDIS, E5, ARRIZO, RIICH, J11, TIGGO, BOSS, CROSSEASTAR	Gasoline
CHEVROLET	AVEO, CAPTIVA, LANOS, NIVA, REZZO, VIVA	Gasoline and Diesel before 2006
DACIA	SUPERNOVA, SOLENZA, SANDERO, LOGAN, DUSTER, LODGYM DOKKER	Gasoline before 2004
DAEWOO	MATIZ, NEXIA, GENTRA	Gasoline
DAIHATSU	CUORE, MIRA, CHARADE, TREVIS, MOVE, SIRION, YOUNG RV, MATERIA, TERIOS, COPEN	Gasoline
DATSUN	MI-DO, ON-DO	Gasoline
FIAT	500, DOBLO, 600, SEICENTO, PANDA, PALIO, ALBEA, SIENA, IDEA, PUNTO, LINEA, BARCHETTA, BRAVO, STILO, MAREA, CROMA, SEDICI, MULTIPLA	Gasoline and Diesel without particulate filters before 2010
GAZ	3102, 31029, 3110, SIBER	Gasoline
GEELY	BEAUTY LEOPARD, BORUI, FREE CRUISER, EMGRAND, YUANJIN, VISION, GL EAGLE, HOAQING, LC PANDA, MEIRI ULIOU, KING KONG, JINGYING	Gasoline before 2014
GREAT WALL	FLORID, VOLEEX, COOLBEAR, HAVAL, HOVER	Gasoline before 2011
HONDA	JAZZ, CIVIC, STREAM, ACCORD, LEGEND, HR-V, CR-V, NSX	Gasoline before 2004
HYUNDAI	ACCENT, GETZ, MATRIX, SANTA FE, SONATA, TERRACAN, TUCSON	Gasoline and Diesel before 2008
KIA	CARENS, CARNAVAL, CERATO, MAGENTIS/OPTIMA, PICANTO, SORENTO, SPECTRA/SEPHIA/SHUMA, SPORTAGE	Gasoline and Diesel before 2008
LADA	All models	Gasoline
LIFAN	320, 520, 620, 720	Gasoline
MAZDA	2,3, 323, 6, ATENZA, CAPELLA, DEMIO, FAMILIA, PREMACY	Gasoline Diesel before 2004
MITSUBISHI	AIRTREK, CARISMA, COLT, GALANT, GRANDIS, L200, LANCER, CEDIA, LIBERO, MIRAGE, OUTLANDER, PAJERO, PININ, SPORT, SPACE STAR	Gasoline and Diesel before 2009
NISSAN	ALMERA, CUBE, EVALIA, JUKE, LEAF, MAXIMA QX, MICRA, MARCH, MURANO, NAVARA, NOTE, PATHFINDER, PATROL, TERRANO, PIXA, PULSAR, PRIMERA, QASHQAI, SKYLINE, TEANA, TIIDA, X-TRAIL	Gasoline and Diesel without particulate filters
RENAULT (RUS)	CLIO, DUSTER, FLUENCE, LAGUNA, LOGAN, MEGANE, SANDERO, SCENIC, SYMBOL	Gasoline
SUZUKI	ALTO, CELERIO, WAGON, SPLASH, SWIFT, IGNIS, SX4, LIANA, KIZASHI, JIMNY, VITARA, GRAND VITARA	Gasoline and Diesel without particulate filters before 2005
TAGAZ	VEGA, TAGER	Gasoline
TOYOTA	AVENSIS, CALDINA, CAMRY, CARINA, COROLLA, CORONA, GAIA, HARRIER, HIGHLANDER, HILUX, IPSUM, IST, LAND CRUISER, MARK, NADIA, NOAH, OPA, PLATZ, PREMIO, PRIUS, RAV 4, SUCCEED, VERSO, VISTA, VITZ, WISH, YARIS	Diesel without particulate filters before 2007
UAZ	3151, HUNTER, PATRIOT, PICKUP, CARGO	Gasoline and Diesel
CHERY	QQ6, CHANCE, M, TENGO, A, INDIS, E5, ARRIZO, RIICH, J11, TIGGO, BOSS, CROSSEASTAR	Gasoline

* Third party data is used to determine the recommended products. Gazpromneft Lubricants accepts no liability for the suitability of any recommendation made. Any decisions you make based on this information are your sole responsibility. Before adding any products to your vehicle, please always check vehicle/equipment handbook to confirm the suitability of any product recommendations for your vehicle/equipment.

Gazpromneft Premium L 15W-40 and 20W-50

Passenger Vehicle Engine Oils



Engine oil



Minerals



Engine cleanliness



Gasoline and diesel engines



Multigrade



Advanced polymers

Gazpromneft Premium L 15W-40 and 20W-50 are high quality mineral engine oils providing high level of protection and performance. These oils formulated with improved additive package providing wear, corrosion and rust protection to ensure optimum engine operation. They deliver long engine life for many types and ages of vehicles with enhanced protection over a wide temperature range.

Applications



- Turbo-charged and direct injection high performance engines
- Gasoline and diesel engines without diesel particulate filters (DPF) requiring oil with ACEA A3/B3 or API SL, API CF standards
- Passenger cars, SUV's, light trucks and vans

Features	Advantages and Potential Benefits
Multi-purpose application	High quality formulation suitable for a wide range of vehicles requiring premium quality product
Wear protection	Strong oil film provides protection against wear under all operating conditions for long engine life
Improved thermal and oxidation stability	Helps to resist oil aging allowing extended drain interval protection
Deposit control	Prevents forming of sludge and harmful deposits through the use of advanced detergent additives for engine cleanliness
Stay-in-grade	Keeps protective oil film during the whole drain interval and maintains viscosity grade

Meet the requirements:

- ACEA A3/B3
- API SL
- API CF
- AVTOVAZ (Gazpromneft Premium L 20W-50)

Typical Characteristics

Properties	Method	Gazpromneft Premium L 15W-40	Gazpromneft Premium L 20W-50
SAE Viscosity Grade	SAE J300	15W-40	20W-50
Kinematic Viscosity @40°C, mm ² /s	ASTM D445	114,5	114,5
Kinematic Viscosity @100°C, mm ² /s	ASTM D445	14,8	14,8
Viscosity Index	ASTM D2270	133	120
Flash Point (COC), °C	ASTM D92	236	240
Pour Point, °C	ASTM D97	-30	-29
Total Base Number, mg KOH/g	IP 3016	9,0	9,0
Density @15°C, kg/m ³	ASTM D4052	881	889
Sulfated Ash, wt%	ASTM D874	1,3	1,3

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.