

Gazpromneft Grease LTS Moly EP 2

Multipurpose Extreme Pressure Lithium/Calcium Grease with Molybdenum Disulfide

Gazpromneft Grease LTS Moly EP 2 is multipurpose, extreme pressure grease based on a blend of high viscosity index mineral oils and lithium/calcium soap thickener. It contains extreme pressure, anti-oxidation, anti-wear, anti-corrosion, adhesion additives and molybdenum disulfide to provide resistance to shock loading. Gazpromneft Grease LTS Moly EP 2 is suitable for various shock loaded or vibrating applications in transport, agriculture and off-road equipment, operating in wet, dusty and dry conditions. Gazpromneft Grease LTS Moly EP 2 is recommended for use over the temperature range -30°C to 120°C.

Applications

- Gazpromneft Grease LTS Moly EP 2 is recommended for the lubrication of shock loaded heavy duty bearings working in wet adverse conditions found in transport, agriculture and off-road equipment applications

Features, Advantages & Potential Benefits

- **Outstanding extreme pressure properties**
Reduced wear under heavy or shock loading and vibration for good equipment reliability and availability. The presence of molybdenum disulfide guarantees good lubrication in severe sliding situations
- **Excellent mechanical stability**
Resistance to grease softening with subsequent loss of lubrication performance and leakage
- **Excellent water and corrosion resistance**
Extended bearing life in wet environments for reduced bearing costs and unexpected downtime
- **Very good thermal stability**
High resistance to temperature variations helps extend grease life and reduce maintenance costs

Meet the requirements

Specification	Gazpromneft Grease LTS Moly EP 2
DIN 51502	KPF2K-30

Typical Characteristics

Properties	Method	Gazpromneft Grease LTS Moly EP 2
NLGI Grade		2
Thickener Type		Lithium/Calcium
Color	visual	Grey
Molybdenum Disulfide, wt%	calculated	3
Penetration, worked 60 stokes, mm/10	ASTM D217	265-295
Dropping Point, °C	ASTM D566	>190
Base Oil Viscosity @40°C, mm ² /s	ASTM D445	150
4-Ball Wear Scar Diameter, mm	ASTM D2266	0,4
4-Ball Weld Load, N	ASTM D2596	3600
Rust Protection, distilled water	ASTM D6138	pass

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.

✔ ISO 9001

✔ ISO 14001

✔ ISO/TS 16949

✔ OHSAS 18001

CERTIFIED

GAZPROMNEFT – LUBRICANTS, LTD.
14/3, Krzhyzhanovskogo Street, Moscow, 117218 Russia
Tel: +7 (495) 642-99-69
Fax: +7 (495) 921-48-63

While the information and figures given here are typical of current production and confirm to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the product. To find the right G-Profi product for your vehicle and equipment, please visit G-Energy Oil Assistant at g-energy.org. Advice on application and more information may be obtained from our technical helpdesk. E-mail: Techservice@gazprom-neft.ru. 05/2017