



G-Energy Flushing Oil

Description

G-Energy Flushing Oil is designed for flushing of internal combustion engine oil systems without the need to disassemble the engine before change of oil. It cleans sludge and deposits in crankcase, oil receiver, oil pipes and other engine parts. The product formula contains high purity base oil and multi-purpose additives to ensure excellent flushing and protection.

Benefits

- Provides rapid and effective cleaning of various kinds of residues and contaminants
- Compatible with seal materials
- Protects engine compounds when flushing
- Has no effect on performance of a motor oil filled after

Applications

- Flushing foreign and domestic gasoline and diesel engines (without disassembling) at a scheduled time when the oil is changed and necessarily after the use of oil with poor performance characteristics, as well as when recommended oil change interval is exceeded
- Engines in LADA cars by AVTOVAZ
- To flush an engine warm it up for 20-30 min. of idle running, drain the old motor oil, fill the engine with the flushing oil and run it at idle for 15-25 min. Then discharge the flush oil, change the oil filter and fill the engine with fresh motor oil.

Specifications and Approvals

G-Energy Flushing Oil is approved by:

- AVTOVAZ, JSC

Typical Properties

G-Energy Flushing Oil

| | | |
|--|-------------|-------|
| Viscosity | | |
| • cSt @ 100°C | GOST 33 | 8.02 |
| Flash Point, COC, °C | GOST 4333 | 230 |
| Pour Point, °C | GOST 20287 | -26 |
| Calcium Content, % | ASTM D 6481 | 0.17 |
| Zinc Content, % | ASTM D 6481 | 0.068 |
| Specific Gravity, kg/m ³ @ 20°C | ASTM D 4052 | 880 |

Health and Safety

When used as directed, G-Energy Flushing Oil has no adverse effects either on health or environment. Beyond normal hygiene no special precautions are required. Avoid contact with skin. Use protective gloves. In case of contact, flush immediately with water and soap. For more information please refer to the Safety Data Sheet.



Manufacturer: Gazpromneft MLP CJSC, 6 a, Ozernaya str., Fryazino, Moscow region, 141191, Russia.
All products may not be available locally. For more information, contact your local sales office or visit www.gazpromneft-lubricants.com.
Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly. © 2009 Gazpromneft Lubricants Ltd. All rights reserved.
05.06.2012.

Reduced Environmental Impact

Place used product in an appropriate waste disposal container. Dispose via a licensed waste disposal contractor. Do not discharge waste lubricant into groundwater, watercourses, soil, sewerage or drainage systems.



Manufacturer: Gazpromneft MLP CJSC, 6 a. Ozeraya str., Fryazino, Moscow region, 141191, Russia.
All products may not be available locally. For more information, contact your local sales office or visit www.gazpromneft-lubricants.com.
Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly. © 2009 Gazpromneft Lubricants Ltd. All rights reserved.
05.06.2012.