

Gazpromneft Motor Oil 40, 50 and 60

Passenger Vehicle Engine Oils

Gazpromneft Motor Oil primarily intended for use in gasoline automotive engines of passenger cars, commercial vehicles and farm equipment. They've effective balance of detergents and dispersants to minimize the formation of sludge and deposits, retain alkalinity and reduce wear. Specially engineered for hot climate conditions.

Applications

- Gasoline and diesel engines requiring oil with API SC/CA standards
- Older engine technologies
- Cars, vans, small trucks, light commercial vehicles and farm equipment

| Features | Advantages and Potential Benefits |
|-------------------------------------|--|
| Wear protection | Provides efficient lubrication over a wide range of hot operating conditions |
| Thermal and oxidation stability | Resists oil thickening during whole drain interval |
| Detergent and dispersant properties | Control of high temperature deposits formation to prevent sludge and keep engine cleaner |

Meet the requirements:

- API SC/CA

Typical Characteristics

| Properties | Method | Gazpromneft Motor Oil 40 | Gazpromneft Motor Oil 50 | Gazpromneft Motor Oil 60 |
|--|-------------|--------------------------|--------------------------|--------------------------|
| SAE Viscosity Grade | SAE J300 | 40 | 50 | 60 |
| Kinematic Viscosity @100°C, mm ² /s | ASTM D 445 | 14,9 | 18,5 | 24,6 |
| Flash Point (COC), °C | ASTM D 92 | 232 | 243 | 255 |
| Pour Point, °C | ASTM D 97 | -16 | -13 | -12 |
| Total Base Number, mg KOH/g | ASTM D 2896 | 4,0 | 4,0 | 4,0 |
| Density @20°C, kg/m ³ | ASTM D 4052 | 894 | 896 | 901 |

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.