



M-10DM

Tractor diesel engine oil

DESCRIPTION

This motor oil delivers superior lubrication in high-power turbocharged diesel engines of foreign and domestic freight trucks, logging trucks, large dump trucks and industrial tractors operating in summer under heavy load conditions. The product can be used in non-turbocharged diesels with increased oil change intervals. The oil is formulated with mineral base stocks and progressive additives to ensure proprietary performance characteristics.

BENEFITS

- Excellent resistance to deposits formation even when fuel with increased concentration of sulphur is used
- Stable performance at high temperatures
- Outstanding anti-oxidation, anti-corrosive and anti-wear properties
- Optimum performance in engines running continuously under heavy loads

APPLICATIONS

- Diesel engines in freight trucks, logging trucks, large dump trucks and industrial tractors where the oils of API CD or earlier specifications are required.

SPECIFICATIONS AND APPROVALS

M-10DM complies with:

- API CD



TYPICAL PROPERTIES

<i>Typical Properties</i>	<i>M-10DM</i>
Viscosity, cSt @ 100 °C	15.4
Viscosity Index	93
Flash Point, COC, °C	246
Pour Point, °C	-21
Base Number, mg KOH/g	9.0
Sulphated Ash, %	1.3
Density @ 20 °C, g/cm ³	0.897

HEALTH AND SAFETY

When used as directed, M-10DM oil has no adverse effects either on health or environment. Beyond normal hygiene no special precautions are required. Avoid contact with skin. Wear protective gloves. In case of contact, flush immediately with water and soap. For more information please refer to the Safety Data Sheet.

REDUCED ENVIRONMENTAL IMPACT

Place used product in an appropriate waste disposal container. Dispose via a licensed waste disposal contractor. Do not discharge waste lubricant into groundwater, watercourses, soil, sewerage or drainage systems.