



Diesel Turbo SAE 20 (M-8DM) ***Tractor diesel engine oil***

DESCRIPTION

Diesel Turbo SAE 20 (M-8DM) is high performance winter oil formulated with mineral base stocks and progressive additive system to deliver excellent protection of high-power diesel engines with turbocharger in foreign and domestic freight trucks, logging trucks, large dump trucks and industrial tractors running under severe operating conditions. It is also suitable for use in non-turbocharged diesel engines to extend oil change intervals.

BENEFITS

- Good resistance to lacquer and deposits formation even when sulphur-containing fuels are used
- Stable performance at high temperatures
- Excellent resistance to oxidation, corrosion and wear
- Optimum performance in engines running continuously under heavy loads

APPLICATIONS

- Diesel engines installed in freight trucks, logging trucks, large dump trucks and industrial tractors where oils of API CD or earlier specifications are required.

SPECIFICATIONS AND APPROVALS

Diesel Turbo SAE 20 (M-8DM) complies with:

- API CD



TYPICAL PROPERTIES

<i>Typical Properties</i>	<i>Diesel Turbo SAE 20 (M-8DM)</i>
Viscosity, cSt @ 100 °C	8.4
Viscosity Index	98
Flash Point, COC, °C	236
Pour Point, °C	-32
Base Number, mg KOH/g	9.2
Sulphated Ash, %	1.39
Density @ 20 °C, g/cm ³	0.881

HEALTH AND SAFETY

When used as directed, Diesel Turbo SAE 20 (M-8DM) has no adverse effects either on health or environment. Beyond normal hygiene no special precautions are required. Avoid contact with skin. Wear protective gloves. In case of contact, flush immediately with water and soap. For more information please refer to the Safety Data Sheet.

REDUCED ENVIRONMENTAL IMPACT

Place used product in an appropriate waste disposal container. Dispose via a licensed waste disposal contractor. Do not discharge waste lubricant into groundwater, watercourses, soil, sewerage or drainage systems.