

G-Motion 4T 0W-40

Four-Stroke Engine Oil



Small four-stroke engines



Sludge formation control at low temperatures



Reduction of high temperature deposits



Synthetic



Excellent low temperature performance

G-Motion 4T 0W-40 is high performance synthetic engine oil formulated with modern additives for use in four stroke engines fitted on snowmobiles. It's helping to extend engine life providing high performance reliability to protect your engine against the formation of sludge at low temperatures and deposits at high temperatures. G-Motion 4T 0W-40 designed for use in applications subjected to extremely low ambient temperatures.

Applications



- High performance four-stroke gasoline engines requiring API SN performance (or lower)
- Snowmobiles and gardening equipment operating in severe cold conditions
- Some smaller four-stroke motorcycles
- Not applicable for wet-clutch engines



Features	Advantages and Potential Benefits
Excellent low temperature performance	Instant oil flow at low temperatures provides easy cold starts and optimal lubrication from the first seconds after ignition.
Excellent detergent and dispersant properties	Lower high temperature deposits formation and outstanding engine cleanliness to reduce maintenance costs
Excellent thermal and oxidation stability	Prolonged oil life allowing extended drain interval protection
Protection from rust and corrosion	Long life of valve train and bearing components

Meets the requirements:

- API SN

Typical Characteristics

Properties	Method	G-Motion 4T 0W-40
SAE Viscosity Grade	SAE J300	0W-40
Kinematic Viscosity @ 100°C, mm ² /s	ASTM D445	13,2
Viscosity Index	ASTM D2270	180
CCS @ -35°C, mPa·s	ASTM D5293	5800
Flash Point (COC), °C	ASTM D92	225
Pour Point, °C	ASTM D97	-45
Density @ 15°C, kg/m ³	ASTM D4052	843



*Sequence VG; **ASTM D4684

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.