


## G-Special TO-4 Arctic 0W-20

High Performance Transmission and Drivetrain Lubricants



**G-Special TO-4 Arctic 0W-20** is high performance, heavy duty transmission and drivetrain lubricant formulated to optimize the performance of powershift transmissions, gearboxes, and final drives. In hydraulic applications, they provide maximum protection even in high pressure systems. It made from synthetic base oils and an advanced additive package to provide maximum capacity of construction, quarrying, and mining equipment operating in severe conditions. Specially engineered for extremely cold climate.

### Applications



- Heavy duty transmissions, gear boxes, final drives, and hydraulic systems used in off-highway applications
- Off-highway industries including: mining, construction, quarrying, and agriculture
- Powershift transmissions, hydraulic systems, oil-immersed brakes
- Power takeoff systems, differential units, final drives
- Not applicable for unites where UTTO oils are specified

Features	Advantages and Potential Benefits
Excellent low temperature performance	Low temperature pumpability reduced time from start-up to production. Excellent protection for components during extreme cold temperature operation.
Balanced static and dynamic friction coefficients	Optimized clutch-friction retention and slippage control
Excellent thermal and oxidation stability	Neutralizes acids formed from combustion or oil degradation, protects against high-pressure pump wear for long engine life
Increased levels of anti-wear capability	Reduced gear wear and extended life in transmissions, gearboxes, and final drives
Reliable share stability	Ensure consistent viscosity throughout fluid service life
Compatible with modern clutch materials and elastomers	Longer clutch life and higher performance


### Meets the requirements:

- Caterpillar TO-4
- Allison C-4
- Komatsu Micro-Clutch
- Vickers 35VQ25


## Typical Characteristics

Properties	Method	G-Special TO-4 Arctic 0W-20
SAE Viscosity Grade	SAE J300	0W-20
Kinematic Viscosity @40°C, mm <sup>2</sup> /s	ASTM D445	33,8
Kinematic Viscosity @100°C, mm <sup>2</sup> /s	ASTM D445	6,9
Viscosity Index	ASTM D2270	170
Brookfield Viscosity @-55°C, mPa·s	ASTM D2983	66000
Flash Point (COC), °C	ASTM D92	208
Pour Point, °C	ASTM D97	-60
Density @15°C, kg/m <sup>3</sup>	ASTM D4052	858

Oxidation Stability\*



Low-temperature performance\*\*



\*DKA (CEC-48-A-95); \*\*ASTM D2983

## Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.