

Gazpromneft Steelgrease CS

Multipurpose Extreme Pressure Water Resistant High Temperature Calcium Sulfonate Complex Grease

Gazpromneft Steelgrease CS is multipurpose, extreme pressure grease based on a blend of high viscosity index mineral oils and calcium sulfonate thickener system. It provides excellent thermal stability, oxidation resistance, corrosion protection and extraordinary water resistance. Gazpromneft Steelgrease CS is designed for industrial bearings in wet, high-temperature and heavy load applications. They are available in NLGI grades 1 and 2. Gazpromneft Steelgrease CS is recommended for use over the temperature range -30°C to 200°C.

Applications

- Gazpromneft Steelgrease CS is recommended for ball and roller bearings in machinery operating at high temperatures where resistance to water washout and corrosion are required, e.g. steel mill and mining operations

Features, Advantages & Potential Benefits

- **Outstanding resistance to water and corrosion**
The calcium sulfonate thickener protects against water washout and bearing corrosion under extreme conditions
- **High load carrying properties**
Excellent extreme pressure protection at low to moderate speeds for good equipment reliability and availability
- **Excellent mechanical stability**
Resistance to grease softening in the presence of water with subsequent loss of lubrication performance and leakage
- **Excellent thermal stability and oxidation resistance**
Extended service life with longer intervals between refilling and improved bearing life

Meet the requirements

Specification	Gazpromneft Steelgrease CS 1	Gazpromneft Steelgrease CS 2
DIN 51502	KP1S-30	KP2S-30

Typical Characteristics

Properties	Method	Gazpromneft Steelgrease CS 1	Gazpromneft Steelgrease CS 2
NLGI Grade		1	2
Thickener Type		Calcium Sulfonate Complex	Calcium Sulfonate Complex
Color	visual	Brown	Brown
Penetration, worked 60 stokes, mm/10	ASTM D217	310-340	265-295
Dropping Point, °C	ASTM D566	>300	>300
Base Oil Viscosity @40°C, mm ² /s	ASTM D445	150	150
4-Ball Wear Scar Diameter, mm	ASTM D2266	0,5	0,5
4-Ball Weld Load, N	ASTM D2596	4000	4000
Rust Protection, distilled water	ASTM D6138	pass	pass
Water Washout, wt%	ASTM D1264	2	2

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.

✔ ISO 9001

✔ ISO 14001

✔ ISO/TS 16949

✔ OHSAS 18001

CERTIFIED

GAZPROMNEFT – LUBRICANTS, LTD.
14/3, Krzhyzhanovskogo Street, Moscow, 117218 Russia
Tel: +7 (495) 642-99-69
Fax: +7 (495) 921-48-63

While the information and figures given here are typical of current production and confirm to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the product. To find the right G-Profi product for your vehicle and equipment, please visit G-Energy Oil Assistant at g-energy.org. Advice on application and more information may be obtained from our technical helpdesk. E-mail: Techservice@gazprom-neft.ru. 05/2017