



Gazpromneft Super SAE 5W-40, 10W-40, 10W-30, 15W-40 Multigrade engine oils

DESCRIPTION

Semi-synthetic Gazpromneft Super 5W-40 and Gazpromneft Super 10W-40, and mineral Gazpromneft Super 10W-30 and Gazpromneft Super 15W-40 engine oils are blended with high quality base stocks and balanced additive system. Advanced base oils ensure extended service life, reduced oil consumption through burning and enhanced wear protection.

Gazpromneft Super 10W-30 delivers improved fuel economy compared with other engine oils in the Gazpromneft Super range.

BENEFITS

- Good temperature-viscosity dependence guarantees trouble-free start of engine, high oil feed rates in winter conditions and efficient lubrication in operating temperature range
- High thermal and oxidation stability
- Advanced anti-wear protection, minimum sludge and deposits formation
- Good protection against corrosion, deposits and wear when recommended change interval is followed

APPLICATIONS

- Gasoline and diesel engines (with turbocharger or not) of foreign and domestic cars, light trucks and vans, where the use of API SG/CD or earlier specification oils featuring SAE 5W-40, 10W-40, 10W-30 and 15W-40 viscosity grades is recommended.

SPECIFICATIONS AND APPROVALS

Gazpromneft Super oils comply with/approved by:

- API SG/CD
- AVTOVAZ
- Russian Association of Automotive Engineers



TYPICAL PROPERTIES

<i>Typical Properties</i>	<i>Gazpromneft Super 5W-40</i>	<i>Gazpromneft Super 10W-40</i>	<i>Gazpromneft Super 10W-30</i>	<i>Gazpromneft Super 15W-40</i>
Viscosity, cSt @ 100 °C	14,3	14,2	11,5	14,3
Viscosity, cSt @ 40 °C	89,1	98,3	78,1	109,1
Viscosity Index	167	148	139	133
Flash Point, COC, °C	231	229	223	234
Pour Point, °C	-39	-37	-36	-34
Base Number, mg KOH/g	6,0	6,0	6,0	6,0
Sulphated Ash, %	0,9	0,9	0,9	0,9
Density @ 20 °C, g/cm ³	0,860	0,874	0,876	0,880

HEALTH AND SAFETY

When used as directed, Gazpromneft Super oils have no adverse effects either on health or environment. Beyond normal hygiene no special precautions are required. Avoid contact with skin. Wear protective gloves. In case of contact, flush immediately with water and soap. For more information please refer to the Safety Data Sheet.

REDUCED ENVIRONMENTAL IMPACT

Place used product in an appropriate waste disposal container. Dispose via a licensed waste disposal contractor. Do not discharge waste lubricant into groundwater, watercourses, soil, sewerage or drainage systems.