


G-Special STOU 10W-30

Super Tractor Oil Universal



G-Special STOU 10W-30 is semisynthetic extra high performance premium multi-functional oil specially formulated for use in agricultural equipment, engines, transmissions, and differentials with wet brake system and integrated hydraulic system. The product can be used for total tractor lubrication and meets the requirement of many tractor manufacturers.

Applications



- Total tractor lubrication, engine, gearbox, differential, hydraulic system
- Tractors with wet brake system
- Power take-offs
- Harvesting equipment
- Combines, earthmoving machines, forklifts

Features	Advantages and Potential Benefits
Multipurpose product	One oil for many lubricant applications
Excellent thermal and oxidation stability	Reduces deposits, extends seal life, and increases service life of equipment and lubricant
Wear protection	The carefully chosen base oils and additive system form a protective oil film for all the tractor components for extended service life
Effective frictional and load carrying properties	Improved power train performance and elimination of chatter in wet brakes
Excellent low temperature performance	Easier engine start-up, reduced wear in critical valve train and good hydraulic response
Good rust and corrosion protection	Long equipment life especially in hydraulic components
Compatible with clutch materials and elastomers	Longer clutch life and reduced leakage

Meets the requirements:

- ACEA E3
- Allison C-4
- API CD/SE, CD/SF, CE/SF, CF, CF-4, CG-4
- API GL-4
- Caterpillar TO-2
- CCMC D4
- Ford ESN M2C 134-A, M2C 159 B&C, M2C 86 B
- Ford New Holland NH 82009201, NH 82009202
- John Deere JDM J27
- MAN 271
- Massey Ferguson CMS M1127A, M1135, M1139, M1144, M1145
- New Holland NH 410B, NH 420A
- Sauer Sunstrand/Danfoss Hydro Static Trans Fluid
- Sperry Vickers/Eaton I-280-S
- Sperry Vickers/Eaton M2950S

Typical Characteristics

Properties	Method	G-Special STOU 10W-30
SAE Viscosity Grade	SAE J300	10W-30
Kinematic Viscosity @40°C, mm ² /s	ASTM D445	80,0
Kinematic Viscosity @100°C, mm ² /s	ASTM D445	11,9
Viscosity Index	ASTM D2270	143
Brookfield Viscosity @-35°C, mPa·s	ASTM D2983	<7000
Flash Point (COC), °C	ASTM D92	228
Pour Point, °C	ASTM D97	-37
Density @15°C, kg/m ³	ASTM D4052	875

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.