



M-14V2

Diesel engine oil

DESCRIPTION

Formulated with mineral base oils and balanced additive system M-14V2 delivers required lubricating performance in two and four-stroke diesel engines of locomotive, marine and stationary machinery using distillate fuel with 0.5% sulphur concentration. The oil can be used also in open-pit dump truck engines.

BENEFITS

- Good resistance to deposits formation, low evaporation losses and low consumption through burning
- Stable performance at high temperature

APPLICATIONS

- Two and four-stroke diesel engines used in locomotive, marine and stationary machinery
- Diesel engines in open-pit dump trucks, where the oils of API CB or earlier specifications are required.

SPECIFICATIONS AND APPROVALS

M-14V2 complies with:

- API CB



TYPICAL PROPERTIES

<i>Typical Properties</i>	<i>M-14V2</i>
Viscosity, cSt @ 100 °C	14.0
Viscosity Index	92
Flash Point, COC, °C	246
Pour Point, °C	-17
Base Number, mg KOH/g	6.3
Sulphated Ash, %	0.9
Density @ 20 °C, g/cm ³	0.894
Color (15:85 solution)	2.0

HEALTH AND SAFETY

When used as directed, M-14V2 oil has no adverse effects either on health or environment. Beyond normal hygiene no special precautions are required. Avoid contact with skin. Wear protective gloves. In case of contact, flush immediately with water and soap. For more information please refer to the Safety Data Sheet.

REDUCED ENVIRONMENTAL IMPACT

Place used product in an appropriate waste disposal container. Dispose via a licensed waste disposal contractor. Do not discharge waste lubricant into groundwater, watercourses, soil, sewerage or drainage systems.