

## Gazpromneft Moto 4T 30

Four-Stroke Engine Oil



Engine oil



Mineral



Engine cleanliness



Small 4T engines



Wear protection



Excellent friction performance

**Gazpromneft Moto 4T 30** is high quality mineral oil designed for many types of small four-stroke engines. It formulated with highly refined mineral oils and thoroughly selected additives to provide complete protection against wear and corrosion and meet the lubrication needs of small four stroke engines.

### Applications



- Small four-stroke gasoline and diesel engines requiring API SF or API CD performance (or lower)
- Lawnmowers, generator sets and pumps, brushcutters and other gardening equipment that specify this viscosity grade
- Four stroke outboard/inboard air-cooled engines

Features	Advantages and Potential Benefits
Wear protection	Protection throughout the range of operating conditions to extend engine life
Thermal and oxidation stability	Resists oil thickening during whole drain interval
Detergent and dispersant properties	Control deposits formation to prevent sludge and keep engine cleaner
Good corrosion protection	Protects critical engine components

### Meet the requirements:

- API SG
- API CD

### Typical Characteristics

Properties	Method	Gazpromneft Moto 4T 30
SAE Viscosity Grade	SAE J300	20W-50
Kinematic Viscosity @100°C, mm <sup>2</sup> /s	ASTM D445	11,2
Flash Point (COC), °C	ASTM D92	230
Pour Point, °C	ASTM D97	-30
Total Base Number, mg KOH/g	IP 3016	6,1
Density @15°C, kg/m <sup>3</sup>	ASTM D4052	893
Sulfated Ash, wt%	ASTM D874	0,8

### Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.