



## ***Gazpromneft Promo*** ***Engine flushing oil***

### **DESCRIPTION**

The flushing oil is designed for gas and diesel engine oil systems in foreign and domestic vehicles. It cleans sludge and deposits in crankcase, oil receiver, oil pipes and other engine parts. It is recommended to flush the engine at a scheduled time when the oil is changed and necessarily after oil featuring poor performance characteristics is used, as well as when recommended oil change interval is exceeded.

### **BENEFITS**

- High performance additive system provides good flushing and dissolving properties
- Flushing process takes 20-30 min. of warm idle running
- Protects against wear during the treatment

### **SPECIFICATIONS AND APPROVALS**

**Gazpromneft Promo oil is approved by:**

- AVTOVAZ, JSC



Gazpromneft Lubricants Ltd., Russia, 117647, Moscow, Profsoyuznaya St., bld.125A. Gazpromneft Lubricants' Standard # 84035624-070-2012  
For more information please contact our technical personnel:

e-mail: [Techservice@gazprom-neft.ru](mailto:Techservice@gazprom-neft.ru)

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. The information contained herein is subject to changes without notification.

16.08.2012



## TYPICAL PROPERTIES

<i>Typical Properties</i>	<i>Gazpromneft Promo</i>
Viscosity, cSt @ 100 °C	10.0
Flash Point, COC, °C	232
Pour Point, °C	-24
Density @ 20 °C, g/cm <sup>3</sup>	0.885
<ul style="list-style-type: none"><li>▪ Calcium Content % mass</li><li>▪ Zinc Content % mass</li></ul>	 0.11 0.08
Flushing Efficiency	Pass

## HEALTH AND SAFETY

When used as directed, Gazpromneft Promo oil has no adverse effects either on health or environment. Beyond normal hygiene no special precautions are required. Avoid contact with skin. Wear protective gloves. In case of contact, flush immediately with water and soap. For more information please refer to the Safety Data Sheet.

## REDUCED ENVIRONMENTAL IMPACT

Place used product in an appropriate waste disposal container. Dispose via a licensed waste disposal contractor. Do not discharge waste lubricant into groundwater, watercourses, soil, sewerage or drainage systems.