



## ***Gazpromneft Moto 2T*** ***Two-stroke engine oil***

### **DESCRIPTION**

The oil is intended for the lubrication of air-cooled two-stroke gasoline engines that are used in motorcycles, scooters, snowmobiles, power boats, two-wheel tractors, as well as chain saws, power mowers and other gardening equipment. The product is used for mixing with fuel – 1:50 to 1:100 solutions depending on operating conditions and OEM's recommendations. It reduces carbon deposition and toxic emissions and delivers excellent protection against piston and cylinder wear.

### **BENEFITS**

- Delivers superior mixability and solubility when mixed with gas; stable oil film on piston and cylinder surfaces
- Exhibits excellent wear protection and resistance to engine and exhaust port deposits; prevents spark plug fouling, ring sticking and cylinder scuffing; extends engine life and retains its maximum capacity
- Well-balanced oil composition promotes cleaner combustion and reduces toxic emissions
- Provides outstanding protection against corrosion during lengthy downtime

### **SPECIFICATIONS AND APPROVALS**

**Gazpromneft Moto 2T complies with:**

- JASO FB
- ISO-L-EGB



## TYPICAL PROPERTIES

<i>Typical Properties</i>	<i>Gazpromneft Moto 2T</i>
Viscosity, cSt @ 100 °C	8,4
Viscosity, cSt @ 40 °C	67,4
Pour Point, °C	-20
Flash Point, COC, °C	186
Sulphated Ash, %	0,06
Density @ 20 °C, g/cm <sup>3</sup>	0,880

## HEALTH AND SAFETY

When used as directed, Gazpromneft Moto 2T oil has no adverse effects either on health or environment. Beyond normal hygiene no special precautions are required. Avoid contact with skin. Wear protective gloves. In case of contact, flush immediately with water and soap. For more information please refer to the Safety Data Sheet.

## REDUCED ENVIRONMENTAL IMPACT

Place used product in an appropriate waste disposal container. Dispose via a licensed waste disposal contractor. Do not discharge waste lubricant into groundwater, watercourses, soil, sewerage or drainage systems.