



Gazpromneft Moto 2T

Two-Stroke Engine Oil



Engine oil



Mineral



Engine cleanliness



Small 2T gasoline engines



Low ash formulation



Excellent friction performance

Gazpromneft Moto 2T is high quality two-stroke engine oil that has been developed for small to medium size air-cooled two-stroke engines. Gazpromneft Moto 2T is formulated with modern low ash additive system which offers protection against scuffing of piston rings and liner wear by minimizing piston ring deposits. Mixing with the fuel should be in accordance with the manufacturer's recommendations.

Applications



- Land based air-cooled two-stroke engines
- Two-stroke engines where JASO FB oils are recommended
- Motorcycles, go-karts, snowmobiles
- Lean oil/fuel ratio chain saws, lawnmowers and other gardening equipment

Features	Advantages and Potential Benefits
Cleaner combustion and reduced deposits in combustion area	Reduces plug fouling and exhaust port deposits help to minimize pre-ignition and extend spark plug and valve life
Reduced Smoke	Less smoke to improve environmental concerns and riding comfort
High temperature deposits control	Cleaner engines resulting in reduced ring sticking and cylinder scuffing, and extended engine life
Wear protection	Good film strength under a full range of engine operating conditions protecting against cylinder scuffing and bearing wear resulting in increased engine life

Meet the requirements:

- ISO-L-EGB
- JASO FB

Typical Characteristics

Properties	Method	Gazpromneft Moto 2T
Color	visually	red
Kinematic Viscosity @40°C, mm ² /s	ASTM D445	67,4
Kinematic Viscosity @100°C, mm ² /s	ASTM D445	8,4
Flash Point (COC), °C	ASTM D92	186
Pour Point, °C	ASTM D97	-20
Density @15°C, kg/m ³	ASTM D4052	884
Sulfated Ash, wt%	ASTM D874	0,06

ISO 9001

ISO 14001

ISO/TS 16949

OHSAS 18001

CERTIFIED

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.