



G-Box GL-4 75W-90

Product Description

G-Box GL-4 75W-90 – transmission oil designed to work in car and truck mechanical transmission units. Made on the basis of high quality basic composition of synthetic and mineral oils using high-performance additive package. Provides a wide temperature range of application, and prolonged trouble-free work of transmission units.

Benefits

- Optimum frictional properties ensure smooth gear shift and work without vibration.
- It has exceptional low-temperature properties (provides work of transmission units under the temperatures upto -40 ° C).
- High thermal stability ensures increased oil change intervals.
- High anti-wear and anti-corrosion properties of oil significantly extend the transmission lifetime.
- Compatible with gasket and seal materials used in modern technology.

Application

- Intended for use in mechanical transmissions, car gear boxes, transfer boxes of all-wheel drive vehicles containing cylindrical, bevel and spiral-bevel gears.
- For lubrication of units containing hypoid gears working in a moderately severe conditions and where the recommended oil type is API GL-4.

Specifications and Approvals

- API GL-4



Manufacturer: Gazpromneft Lubricants Italia S.p.A. Via Bitritto, km 7.800 - 70124 Bari - Italy.
All products may not be available locally. For more information please contact your local sales office, our technical personnel techservice@gazprom-neft.ru or visit our website www.gazpromneft-lubricants.com. Due to continual product research and development, the information contained herein is subject to change without notification.
Typical properties may vary slightly. © 2009 Gazpromneft-lubricants, Ltd. All rights reserved.
30.05.2016

Physical and Chemical Properties

<i>Kinematic viscosity :</i>		
• at 40 °C, mm ² /s	ASTM D 445	112
• at 100 °C, mm ² /s	ASTM D 445	17,5
Dynamic Viscosity (Brookfield) at -40°C, mPa*s	ASTM D 2983	135000
Viscosity Index	ASTM D 2270	172
Flash point in open cup, °C	ASTM D 92	203
Pour point, °C	ASTM D 97	-42
Density at 15 °C, kg/m ³	ASTM D 1298	883

Health and Safety

Subject to the rules of personal and industrial hygiene, as well as when used properly in the recommended application, G-Box GL-4 75W-90 oil poses no threat to human health and the environment. Avoid skin contact. When changing the oil, use protective gloves/mittens. In case of skin contact wash the oil immediately off with soap and water. For more information on this subject please refer to the product safety data sheet.

Environmental Protection

Waste oil and residual products must be mandatory collected in a sealed container and handed to waste oil acceptance stations. Do not pour waste oil into drains, soil or water.



Manufacturer: Gazpromneft Lubricants Italia S.p.A. Via Bitritto, km 7.800 - 70124 Bari - Italy.
All products may not be available locally. For more information please contact your local sales office, our technical personnel techservice@gazprom-neft.ru or visit our website www.gazpromneft-lubricants.com. Due to continual product research and development, the information contained herein is subject to change without notification.
Typical properties may vary slightly. © 2009 Gazpromneft-lubricants, Ltd. All rights reserved.
30.05.2016