

G-Truck GL-5 80W-90

Heavy Duty Automotive Gear Oil

G-Truck GL-5 80W-90 is high performance, heavy duty gear oil engineered for automotive applications including heavy duty axles and final drives where extreme pressures and shock loading are expected. Formulated from high performance base oils and an advanced additive system it provide excellent resistance toward high temperature oil degradation and oil thickening to help maintain clean bearing surfaces and minimize wear. G-Truck GL-5 80W-90 is recommended for applications where API GL-5 service is required.

Applications



- Heavy duty automotive manual transmissions, axles, and final drives requiring API GL-5 level performance
- On-highway cars and light trucks, heavy duty commercial vehicles including MB, MAN, DAF, Iveco, Volvo, Renault
- Off-highway industries including construction, mining, quarrying, and agriculture
- Other gearboxes, steering gears and variable gearboxes
- Not applicable for synchromesh gear boxes from non-ferrous metals

Features	Advantages and Potential Benefits
Enhanced EP properties	Reduced gear wear and extended life in transmissions, gearboxes, and final drives
Reliable share stability	Ensure consistent viscosity throughout fluid service life
Exceptional thermal stability	Extended gear and bearing life due to minimal deposits
Compatible with typical automotive seals and gaskets	Minimum leakage and reduced contamination
Various grades	Three grades for different speeds, torque, loads to maximize equipment life and optimize operating costs

Meet the requirements:

- API GL-5
- DAF MAT 74002
- Renault Trucks
- Volvo 97310
- ZF TE-ML 05A, 07A, 08

Approvals:

- MB 235.0
- MAN 342 Type M1
- ZF TE-ML 16B, 17B, 19B, 21A

Typical Characteristics

Properties	Method	G-Truck GL-5 80W-90
SAE Viscosity Grade	SAE J306	80W-90
Kinematic Viscosity @ 40°C, mm ² /s	ASTM D 445	372
@ 100°C, mm ² /s	ASTM D 445	25,4
Viscosity Index	ASTM D 2270	89
Flash Point (COC), °C	ASTM D 92	212
Pour Point, °C	ASTM D 97	-24
Density @ 15°C, kg/m ³	ASTM D 4052	913

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.

G-Truck GL-5 85W-90

Heavy Duty Automotive Gear Oil

G-Truck GL-5 85W-90 is high performance, heavy duty gear oil engineered for automotive applications including heavy duty axles and final drives where extreme pressures and shock loading are expected. Formulated from high performance base oils and an advanced additive system it provide excellent resistance toward high temperature oil degradation and oil thickening to help maintain clean bearing surfaces and minimize wear. G-Truck GL-5 85W-90 is recommended for applications where API GL-5 service is required.

Applications



- Heavy duty automotive manual transmissions, axles, and final drives requiring API GL-5 level performance
- On-highway cars and light trucks, heavy duty commercial vehicles including MB, MAN, DAF, Iveco, Volvo, Renault
- Off-highway industries including construction, mining, quarrying, and agriculture
- Other gearboxes, steering gears and variable gearboxes
- Not applicable for synchromesh gear boxes from non-ferrous metals

Features	Advantages and Potential Benefits
Enhanced EP properties	Reduced gear wear and extended life in transmissions, gearboxes, and final drives
Reliable shear stability	Ensure consistent viscosity throughout fluid service life
Exceptional thermal stability	Extended gear and bearing life due to minimal deposits
Compatible with typical automotive seals and gaskets	Minimum leakage and reduced contamination
Various grades	Three grades for different speeds, torque, loads to maximize equipment life and optimize operating costs

Meet the requirements:

- API GL-5
- DAF MAT 74002
- Iveco
- MAN 342 Type M1
- MB 235.0
- ZF TE-ML 05A, 16C, 17B, 19B, 21A

Typical Characteristics

Properties	Method	G-Truck GL-5 85W-90
SAE Viscosity Grade	SAE J306	85W-90
Kinematic Viscosity @ 40°C, mm ² /s	ASTM D 445	147
@ 100°C, mm ² /s		14,4
Viscosity Index	ASTM D 2270	95
Flash Point (COC), °C	ASTM D 92	208
Pour Point, °C	ASTM D 97	-30
Density @ 15°C, kg/m ³	ASTM D 4052	900

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.

G-Truck GL-5 85W-140

Heavy Duty Automotive Gear Oil

G-Truck GL-5 85W-140 is high performance, heavy duty gear oil engineered for automotive applications including heavy duty axles and final drives where extreme pressures and shock loading are expected. Formulated from high performance base oils and an advanced additive system it provide excellent resistance toward high temperature oil degradation and oil thickening to help maintain clean bearing surfaces and minimize wear. G-Truck GL-5 85W-140 is recommended for applications where API GL-5 service is required.

Applications



- Heavy duty automotive manual transmissions, axles, and final drives requiring API GL-5 level performance
- On-highway cars and light trucks, heavy duty commercial vehicles including MB, MAN, DAF, Iveco, Volvo, Renault
- Off-highway industries including construction, mining, quarrying, and agriculture
- Other gearboxes, steering gears and variable gearboxes
- Not applicable for synchromesh gear boxes from non-ferrous metals

Features	Advantages and Potential Benefits
Enhanced EP properties	Reduced gear wear and extended life in transmissions, gearboxes, and final drives
Reliable share stability	Ensure consistent viscosity throughout fluid service life
Exceptional thermal stability	Extended gear and bearing life due to minimal deposits
Compatible with typical automotive seals and gaskets	Minimum leakage and reduced contamination
Various grades	Three grades for different speeds, torque, loads to maximize equipment life and optimize operating costs

Meet the requirements:

- API GL-5
- DAF MAT 74002
- Iveco
- ZF TE-ML 05A, 07A, 08

Approvals:

- Volvo 97310
- ZF TE-ML 16D, 21A

Typical Characteristics

Properties	Method	G-Truck GL-5 85W-140
SAE Viscosity Grade	SAE J306	85W-140
Kinematic Viscosity @ 40°C, mm ² /s @ 100°C, mm ² /s	ASTM D 445	190,6 16,4
Viscosity Index	ASTM D 2270	89
Flash Point (COC), °C	ASTM D 92	210
Pour Point, °C	ASTM D 97	-27
Density @ 15°C, kg/m ³	ASTM D 4052	905

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.