



G-Energy F Synth 5W-30

Fully Synthetic Performance

Product description

G-Energy F Synth 5W-30 is a fully synthetic last-generation engine oil. Thanks to the use of synthetic components of the oil has a high operating reserve. It provides reliable operation and engine protection at various operating conditions, including in urban cycle (Stop-Start). It works in extreme conditions, both at low and high temperatures.

Benefits

- Provides effective lubrication of friction pairs even after prolonged use at maximum speeds and loads
- Superior cleaning and antiwear properties increase engine service life
- High thermal stability ensures reliable performance of the engine and extends oil change intervals
- Low oil consumption through burning thanks to specially selected base components
- Fully compatible with systems of neutralization of exhaust gases, which contributes to a long and effective operation of the catalyst

Application

- for gasoline and diesel engines (including turbocharged ones) of last-generation passenger cars, vans and light trucks
- officially approved by MB, VW, BMW for use in vehicles equipped with engines of these manufacturers
- in the BMW cars with extended oil change intervals (Long life)

Specifications and approvals

- API SM/CF
- ACEA A3/B4
- MB-Approval 229.5
- BMW LL-01
- VW 502 00/505 00
- Renault RN0700
- GM LL-A/B-025



Manufacturer: Gazpromneft Lubricants Italia S.p.A. Via Bitritto, km 7.800 - 70124 Bari - Italy.

All products may not be available locally. For more information, contact your local sales office or visit www.gazpromneft-lubricants.com

Due to continual product research and development, the information contained herein is subject to change without notification.

Typical Properties may vary

slightly. © 2009 "Gazpromneft-lubricants", Ltd. All rights reserved.

15.02.2017

Physical and chemical characteristics

<i>Kinematic Viscosity</i>		
cSt @ 40 °C	ASTM D 445	69
cSt @ 100 °C	ASTM D 445	12,2
Viscosity index	ASTM D 2270	176
Total Base Number, mg KOH/g	ASTM D 2896	11
Flash point, °C	ASTM D 92	238
Pour point, °C	ASTM D 97	-42
Density at 15 °C, kg/m ³	ASTM D 1298	856

Health and safety

Subject to OH&S rules and proper use in the recommended domains, the oil poses no threat to the health and the environment. Avoid skin contact. When changing the oil, use protective gloves/mittens. Upon skin contact immediately wash off the oil with soap and water. For more information on this subject please refer to the product safety data sheet.

Environmental protection

Waste oil and residual products must be at all times collected in a sealed container and handed to waste oil acceptance stations. Do not pour waste oil into drains, soil or water.



Manufacturer: Gazpromneft Lubricants Italia S.p.A. Via Bitritto, km 7.800 - 70124 Bari - Italy.

All products may not be available locally. For more information, contact your local sales office or visit www.gazpromneft-lubricants.com

Due to continual product research and development, the information contained herein is subject to change without notification.

Typical Properties may vary

slightly. © 2009 "Gazpromneft-lubricants", Ltd. All rights reserved.

15.02.2017