

G-Energy F Synth 5W-30

Premium Fully Synthetic Passenger Vehicle Engine Oil



Adaptive Formula



Engine oil



Fully synthetic



Multigrade



Gasoline and diesel engines



Driving comfort



Engine cleanliness

G-Energy F Synth 5W-30 is fully synthetic engine oil formulated for the highest level of protection demanded by high performance engines. It protects better than conventional engine oils in hot or cold operating temperatures helping to prevent dirt and build-up, for better response and improved performance, thus helping your engine to operate at its full potential.

Applications



- Turbo-charged and direct injection high performance engines
- Gasoline and diesel engines without diesel particulate filters (DPF)
- Passenger cars, SUV's, light trucks and vans
- Highway cruising and stop and go city driving
- Normal to frequently severe operating conditions

	Features	Advantages and Potential Benefits
	Fully synthetic	Excellent overall lubrication and wear protection performance for many driving styles
	Excellent cold start-up performance	Quick cold weather starting helps to extend engine life
	Enhanced thermal and oxidation stability	Outstanding performance during the maximum oil change interval recommended in a vehicle's owner's manual
	Active cleaning agents	Helps prevent deposits and sludge build-up to enable long engine life
	Improved wear protection	Outstanding wear control during automaker recommended oil change intervals for long component and engine life

Meets the requirements:

- ACEA A3/B4
- API SL/CF
- Fiat 9.55535-G1
- General Motors LL-A/B-025
- Renault RN700

Approvals:

- BMW Longlife-01
- MB 229.5
- VW 502.00
- VW 505.00

Typical Characteristics

Properties	Method	G-Energy F Synth 5W-30
SAE Viscosity Grade	SAE J300	5W-30
Kinematic Viscosity @40°C, mm ² /s	ASTM D445	69,0
Kinematic Viscosity @100°C, mm ² /s	ASTM D445	12,2
Viscosity Index	ASTM D2270	176
Total Base Number, mg KOH/g	ASTM D2896	11
Flash Point (COC), °C	ASTM D92	238
Pour Point, °C	ASTM D97	-42
Density @15°C, kg/m ³	ASTM D4052	886

G-Energy F Synth 5W-30 performance benefits compared to ACEA A3/B4

Valve Train

- Optimized power and fuel consumption (cam wear 33% lower)¹
- Lower sludge formation (rocker cover sludge 13% lower)²

Cylinder-piston group

- Engine cleanliness (piston skirt varnish 22% lower)²
- Excellent overall lubrication (bore polishing 40% lower)¹

Crankshaft

- Excellent cold-start performance (MRV@-35°C 46% lower)⁴
- Leakage control due to elastomer compatibility (volume changes 5 times lower)⁵

Oil Screen

- Protection against oil starvation (oil screen clogging 15 times lower compared to API SN)²
- Engine cleanliness (engine sludge 13% lower)²

1- OM646LA; 2-Sequence VG; 3-VW DI Diesel; 4-CEC L-105; 5-CEC L-39-96

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.

ISO 9001

ISO 14001

ISO/TS 16949

OHSAS 18001

CERTIFIED

G-Energy F Synth 5W-30 recommendations*

Makes	Models	Engines
AUDI	A1, A3, A4, A5, A6, A7, A8, Q1, Q3, Q5, Q7	Gasoline; Diesel before 2000
BMW	GT, Series1, Series3, Series5, Series7, X1,X3, X5, X6	Gasoline; Diesel before 2004
CHEVROLET	AVEO,CAPTIVA, LANOS, NIVA, REZZO, VIVA	Gasoline and Diesel before 2006
CITROEN	C1, C2, C3, C4, C5, C6, C8, DS3, DS4, DS5	Gasoline (except THP, VT1, PureTech types); Diesel before 2005
DACIA	SUPERNOVA, SOLENZA, SANDERO, LOGAN, DUSTER, LODGYM DOKKER	Gasoline
DAEWOO	MATIZ, NEXIA, GENTRA	Gasoline
DAIHATSU	CUORE, MIRA, CHARADE, TREVIS, MOVE, SIRION, YOUNG RV, MATERIA, TERIOS, COPEN	Gasoline
DATSUN	MI-DO, ON-DO	Gasoline
FIAT	500, DOBLO, 600, SEICENTO, PANDA, PALIO, ALBEA, SIENA, IDEA, PUNTO, LINEA, BARCETTA, BRAVO, STILO, MAREA, CROMA, SEDICI, QUBO, MULTIPLA, FREEMONT	Gasoline and Diesel without particulate filters before 2010
GAZ	3102, 31029, 3110, SIBER	Gasoline
GEELY	BEAUTY LEOPARD, BORUI, FREE CRUISER, EMGRAND, YUANJIN, VISION, GL EAGLE, HOAQING, LC PANDA, MEIRI ULIOU, KING KONG, JINGYING	Gasoline
GREAT WALL	HAVAL, FLORID, VOLEEX, COOLBEAR, HAVAL, TENGYI, HOVER	Gasoline
HONDA (EU)	JAZZ, CIVIC, STREAM, ACCORD, LEGEND, HR-V, CR-V, NSX	Gasoline; Diesel before 2011
HYUNDAI	ACCENT, ELANTRA, GETZ, I20, I30, I40 IX35, IX55, MATRIX, SANTA FE, SOLARIS, SONATA, TERRACAN, TUCSON, VERNA	Gasoline and Diesel without particulate filters
INFINITI	G, I, JX, M, Q, EX, FX, QX	Gasoline
KIA	CARENS, CARNAVAL, CEED, CERATO, MAGENTIS/OPTIMA, PICANTO, RIO, SORENTO, SOUL, SPECTRA/SEPHIA/SHUMA, SPORTAGE, VENGA	Gasoline and Diesel without particulate filters
LADA	All	Gasoline
LIFAN	320, 520, 620, 720	Gasoline
MAZDA	2,3, 323, 5,6, ATENZA, AXELLA, CAPELLA, CX-3, CX-5, CX-7, CX-9, DEMIO, FAMILIA, PREMACY, VERISA	Gasoline; Diesel before 2004
MERCEDES-BENZ	A, B, C, E, S, SLK, SLC, SL, CLA, CLC, CLK, CLS, CL, GLA, GLK, GLC, M, GLE, R, G, GL, GLS	Gasoline and Diesel without particulate filters
MINI	AIRTRAK, ASX, CARISMA, COLT, DION, GALANT, GRANDIS, L200, LANCER, CEDIA, LIBERO, MIRAGE, OUTLANDER, PAJERO, PININ, SPORT, SPACE STAR	Gasoline; Diesel before 2009
NISSAN	ALMERA, CUBE, EVALIA, JUKE, LEAF, MAXIMA QX, MICRA, MARCH, MURANO, NAVARA, NOTE, PATHFINDER, PATROL, TERRANO, PIXA, PULSAR, PRIMERA, QASHQAI, SKYLINE, TEANA, TIIDA, X-TRAIL	Gasoline and Diesel without particulate filters
OPEL (RUS)	ANTARA, ASTRA, CORSA, INSIGNIA, MERIVA, MOKKA, VECTRA, ZAFIRA	Gasoline and Diesel
RENAULT	CLIO, DUSTER, FLUENCE, LAGUNA, LOGAN, MEGANE, SANDERO, SCENIC, SYMBOL	Gasoline and Diesel without particulate filters
SEAT	MII, AROSA, IBIZA, LEON, CORDOBA, EXEO, TOLEDO, ALTEA, ALHAMBRA	Gasoline; Diesel before 2000
SKODA	FABIA, OCTAVIA, RAPID, ROOMSTER, SUPERB, YETI	Gasoline; Diesel before 2000
SSANGYONG	ACTYON, CHAIRMAN, KORANDO, KYRON, MUSSO, REXTON, RODIUS	Gasoline and Diesel without particulate filters
SUZUKI	ALTO, CELERIO, WAGON, SPLASH, SWIFT, IGNIS, SX4, LIANA, KIZASHI, JIMNY, VITARA, GRAND VITARA	Gasoline
TAGAZ	VEGA, TAGER	Gasoline
TOYOTA	AVENSIS, CALDINA, CAMRY, CARINA, COROLLA, CORONA, GAIA, HARRIER, HIGHLANDER, HILUX, IPSUM, IST, LAND CRUISER, MARK, NADIA, NOAH, OPA, PLATZ, PREMIO, PRIUS, RAV 4, SUCCEED, VERSO, VISTA, VITZ, WISH, YARIS	Diesel without particulate filters before 2007
UAZ	3151, HUNTER, PATRIOT, PICKUP, CARGO	Gasoline and Diesel
VOLKSWAGEN	AMAROCK, BORA, GOLF, JETTA, PASSAT, POLO, SHARAN, TIGUAN, TOUAREG, TOURAN	Gasoline; Diesel before 2000

* Third party data is used to determine the recommended products. Gazpromneft Lubricants accepts no liability for the suitability of any recommendation made. Any decisions you make based on this information are your sole responsibility. Before adding any products to your vehicle, please always check vehicle/equipment handbook to confirm the suitability of any product recommendations for your vehicle/equipment.

ISO 9001

ISO 14001

ISO/TS 16949

OHSAS 18001

CERTIFIED

GAZPROMNEFT – LUBRICANTS, LTD.
14/3, Krzhizhanovskogo Street, Moscow, 117218 Russia
Tel: +7 (495) 642-99-69
Fax: +7 (495) 921-48-63
www.gazpromneft-oil.com

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. The information contained is subject to change without notice. Gazpromneft-Lubricants accept no liability for any damage or loss resulting from using the product in purposes other than it intended, from any failure to comply with the recommendations or from hazards inherent in the nature of the material. If you require any further information please consult our technical helpdesk. E-mail: OilSupport@gazprom-neft.ru 05/2018