

Gazpromneft Chain Oil

Chain and Bar Oil

Gazpromneft Chain Oil is formulated specifically for lubricating chains, guide bars and sprockets of industrial or residential use chain and electric saws. Gazpromneft Chain Oil helps to extend chain and bar life by providing a tacky stay-in-place film of oil that lubricates, cleans and cools the moving parts. It reduces dripping and “throw-off” by their adhesive and stringy nature.

Applications

- Chain saw bar and chain lubrication
- Guide bars and sprockets
- Gazpromneft Chain Oil can be used at ambient temperatures, down to -25°C
- Gazpromneft Chain Oil is not designed as chain saw engine lubricants; it could lead to serious wear and engine failures

Features, Advantages & Potential Benefits

- **Tackiness**
Reduces fling off and consumption
- **Long-term rust and corrosion protections**
Protect the chain and bar from rusting
- **Excellent metal wetting ability**
Complete oil coverage of guide bar and chain to extend saw chain life
- **Improve anti-wear protection**
Helps to prevent damaging metal-to-metal contact between chains, guide bars and drive sprockets

Typical Characteristics

Properties	Method	Gazpromneft Chain Oil
Kinematic Viscosity @40°C, mm ² /s	ASTM D 445	68,0
Kinematic Viscosity @100°C, mm ² /s	ASTM D 445	11,0
Pour Point, °C, max	ASTM D 97	-27
Flash Point, °C	ASTM D 92	215
Density @15°C, kg/m ³	ASTM D 4052	885

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.