



M-10V2

Tractor diesel engine oil

DESCRIPTION

This motor oil delivers superior lubrication in non-turbocharged diesel engines and medium-duty diesel engines for summer operating conditions. The oil is formulated with mineral base stocks and progressive additives to ensure required performance characteristics.

BENEFITS

- Superior resistance to deposits formation ensures cleanness of cylinder-piston engines
- Carbon deposits prevention
- Low evaporation losses and insignificant consumption through burning

APPLICATIONS

- Car and tractor non-turbocharged diesel engines and medium-duty diesel engines, where oils of API CB or earlier specifications are required.

SPECIFICATIONS AND APPROVALS

M-10V2 complies with:

- API CB



TYPICAL PROPERTIES

<i>Typical Properties</i>	<i>M-10V2</i>
Viscosity, cSt @ 100 °C	11.1
Viscosity Index	92
Flash Point, COC, °C	237
Pour Point, °C	-17
Base Number, mg KOH/g	6.8
Sulphated Ash, %	1.1
Density @ 20 °C, g/cm ³	0.892
Color (15:85 solution)	1.5

HEALTH AND SAFETY

When used as directed, M-10V2 oil has no adverse effects either on health or environment. Beyond normal hygiene no special precautions are required. Avoid contact with skin. Wear protective gloves. In case of contact, flush immediately with water and soap. For more information please refer to the Safety Data Sheet.

REDUCED ENVIRONMENTAL IMPACT

Place used product in an appropriate waste disposal container. Dispose via a licensed waste disposal contractor. Do not discharge waste lubricant into groundwater, watercourses, soil, sewerage or drainage systems.