

Gazpromneft Standard 10W-40, 15W-40 and 20W-50

Passenger Vehicle Engine Oils



Engine oil



Mineral



Multigrade



Gasoline and diesel engines



Normal system operating pressure

Gazpromneft Standard oils are high quality mineral engine lubricants providing reliable protection under a wide variety of operating conditions. They contain an effective balance of detergents and dispersants to minimize the formation of sludge and deposits, retain alkalinity and reduce wear.

Applications



- Gasoline and diesel engines without diesel particulate filters (DPF) requiring oil with API SF/CC standards
- Older engine technologies
- Passenger cars, light trucks, farm equipment

Features	Advantages and Potential Benefits
Multi-purpose application	Suitable for a wide range of vehicles
Wear protection	Proven anti-wear additives protect throughout the range of operating conditions for prolonged engine life
Thermal and oxidation stability	Resists oil thickening during whole drain interval
Detergent and dispersant properties	Control of high temperature deposits formation to prevent sludge and keep engine cleaner

Meet the requirements:

- API SF/CC
- AVTOVAZ

Typical Characteristics

Properties	Method	Gazpromneft Standard		
		10W-40	15W-40	20W-50
SAE Viscosity Grade	SAE J300	10W-40	15W-40	20W-50
Kinematic Viscosity @40°C, mm ² /s	ASTM D445	96,1	109,5	169,2
Kinematic Viscosity @100°C, mm ² /s	ASTM D445	13,9	14,2	18,4
Viscosity Index	ASTM D2270	147	131	121
Flash Point (COC), °C	ASTM D92	228	232	242
Pour Point, °C	ASTM D97	-36	-34	-28
Total Base Number, mg KOH/g	IP 3016	6,0	6,0	6,0
Density @15°C, kg/m ³	ASTM D4052	876	880	885
Sulfated Ash, wt%	ASTM D874	0,8	0,8	0,8

✓ ISO 9001

✓ ISO 14001

✓ ISO/TS 16949

✓ OHSAS 18001

CERTIFIED

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.

✔ ISO 9001

✔ ISO 14001

✔ ISO/TS 16949

✔ OHSAS 18001

CERTIFIED

GAZPROMNEFT – LUBRICANTS, LTD.
14/3, Krzhyzhanovskogo Street, Moscow, 117218 Russia
Tel: +7 (495) 642-99-69
Fax: +7 (495) 921-48-63
www.gazpromneft-oil.com

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. The information contained is subject to change without notice. Gazpromneft-Lubricants accept no liability for any damage or loss resulting from using the product in purposes other than it intended, from any failure to comply with the recommendations or from hazards inherent in the nature of the material. If you require any further information please consult our technical helpdesk. E-mail: OilSupport@gazprom-neft.ru 05/2018