



Gazpromneft Premium C3 5W-30

High Performance Passenger Vehicle Engine Oil



Engine oil



Synthetic



Multigrade



Gasoline and diesel engines



Diesel Particulate Filters compatibility



Advanced polymers

Gazpromneft Premium C3 5W-30 is fully synthetic engine oil designed to provide long engine life through enhanced lubrication and protection of critical engine parts. It also provides enhanced protection for the latest emission control systems and turbochargers. Gazpromneft Premium C3 5W-30 can be used in modern GM, MB, BMW and VW Group gasoline and diesel engines.

Applications



- Turbo-charged and direct injection high performance engines
- Cars with environmental friendly exhaust systems, like EGR and TWC, DPF
- Passenger cars, SUV's, light trucks and vans

Features	Advantages and Potential Benefits
Broad vehicle application	High quality formulation suitable for a wide range of vehicles requiring premium quality product
Low ash additive package	Optimized for use with emission control systems like DPF (Diesel Particulate Filter) and TWC (Three Way Catalyst) to keep them in optimal conditions
Excellent low temperature performance	Instant oil flow at low temperatures provides easy cold starts and optimal lubrication from the first seconds after ignition
Wear protection	Strong oil film provides protection against wear under all operating conditions for long engine life
Deposit control	Prevents forming of sludge and harmful deposits through the use of advanced detergent additives for engine cleanliness

Meet the requirements:

- ACEA C3
- API SN (licensed)
- BMW Longlife-04
- MB 229.52
- VW 502.00
- VW 505.00
- VW 505.01

Approvals:

- General Motors dexos2™
- MB 229.51

Typical Characteristics

Properties	Method	Gazpromneft Premium C3 5W-30
SAE Viscosity Grade	SAE J300	5W-30
Kinematic Viscosity @40°C, mm ² /s	ASTM D445	70,8
Kinematic Viscosity @100°C, mm ² /s	ASTM D445	12,1
Viscosity Index	ASTM D2270	169
Flash Point (COC), °C	ASTM D92	241
Pour Point, °C	ASTM D97	-38
Total Base Number, mg KOH/g	ASTM D2896	7,6
Density @15°C, kg/m ³	ASTM D4052	853
Sulfated Ash, wt%	ASTM D874	0,8

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.

Gazpromneft Premium C3 5W-30 recommendations*

Makes	Models	Engines
AUDI	A1, A3, A4, A5, A6, A7, A8, Q1, Q3, Q5, Q7	Gasoline Diesel before 2004
BMW	GT, Series1, Series3, Series5, Series7, X1,X3, X5, X6	Gasoline and Diesel
CADILLAC	BLS, ATS, CTS, XTS, XLR, ELR, STS, SRX, ESCALADE	Gasoline and Diesel
CHEVROLET	AVEO,CAPTIVA, CRUZE, EPICA, LACETTI, LANOS, NIVA, ORLANDO, REZZO, SPARK, VIVA	Gasoline and Diesel c 2007
CITROEN	C1, C2, C3, C4, C5, C6, C8, DS3, DS4, DS5	Gasoline (except THP, VTI, PureTech), Diesel before 2009
DACIA	SUPERNOVA, SOLENZA, SANDERO, LOGAN, DUSTER, LODGYM DOKKER	Diesel with particulate filters
DAEWOO	MATIZ, NEXIA, GENTRA	Gasoline
DAIHATSU	CUORE, MIRA, CHARADE, TREVIS, MOVE, SIRION, YOUNG RV, MATERIA, TERIOS, COPEN	Gasoline
DATSUN	MI-DO, ON-DO	Gasoline
DODGE	CALIBER, AVENGER	Diesel
FIAT	500, DOBLO, 600, SEICENTO, PANDA, PALIO, ALBEA, SIENA, IDEA, PUNTO, LINEA, BARCHETTA, BRAVO, STILO, MAREA, CROMA, SEDICI, QUBO, MULTIPLA, FREEMONT	Gasoline and Diesel before 2012
GAZ	3102, 31029, 3110, SIBER	Gasoline
GEELY	BEAUTY LEOPARD, BORUI, FREE CRUISER, EMGRAND, YUANJIN, VISION, GL EAGLE, HOAQING, LC PANDA, MEIRI ULIOU, KING KONG, JINGYING	Gasoline before 2014
GREAT WALL	HAVAL, FLORID, VOLEEX, COOLBEAR, HAVAL, TENGYI, HOVER	Gasoline
HONDA	JAZZ, CIVIC, FR-V, STREAM, ACCORD, LEGEND, HR-V, CR-V, NSX	Gasoline before 2004 , Diesel with particulate filters
HYUNDAI	ACCENT, ELANTRA, GETZ, I20, I30, I40 IX35, IX55, MATRIX, SANTA FE, SOLARIS, SONATA, TERRACAN, TUCSON, VERNA	Gasoline and Diesel before 2008 Diesel with particulate filters
INFINITI	G, I, JX, M, Q, EX, FX, QX	Gasoline
JEEP	GRAND CHEROKEE	Diesel
KIA	CARENS, CARNAVAL, CEED, CERATO, MAGENTIS/OPTIMA, PICANTO, RIO, SORENTO, SOUL, SPECTRA/SEPHIA/SHUMA, SPORTAGE, VENGA	Gasoline and Diesel before 2008 , Diesel with particulate filters
LADA	All models	Gasoline
MAZDA	2,3, 323, 5,6, ATENZA, AXELLA, CAPELLA, CX-3, CX-5, CX-7, CX-9, DEMIO, FAMILIA, PREMACY, VERISA	Diesel Skyactive
MERCEDES-BENZ	A, B, C, E, S, SLK, SLC, SL, CLA, CLC, CLK, CLS, CL, GLA, GLK, GLC, M, GLE, R, G, GL, GLS	Gasoline and Diesel
MITSUBISHI	AIRTREK, ASX, CARISMA, COLT, DION, GALANT, GRANDIS, L200, LANCER, CEDIA, LIBERO, MIRAGE, OUTLANDER, PAJERO, PININ, SPORT, SPACE STAR	Gasoline before 2009 Diesel with particulate filters
NISSAN	ALMERA, CUBE, EVALIA, JUKE, LEAF, MAXIMA QX, MICRA, MARCH, MURANO, NAVARA, NOTE, PATHFINDER, PATROL, TERRANO, PIXA, PULSAR, PRIMERA, QASHQAI, SKYLINE, TEANA, TIIDA, X-TRAIL	Gasoline and Diesel with particulate filters
PEUGEOT	206, 207, 3008, 307, 308, 406, 407, 408, 508	Gasoline (except THP, VTI, PureTech), Diesel before 2009
OPEL	ANTARA, ASTRA, CORSA, INSIGNIA, MERIVA, MOKKA, VECTRA, ZAFIRA	Gasoline and Diesel
SAAB	9-2, 9-3, 9-5, 9-7	Gasoline and Diesel
SEAT	MII, AROSA, IBIZA, LEON, CORDOBA, EXEO, TOLEDO, ALTEA, ALHAMBRA	Gasoline Diesel (DI) and Diesel before 2006
SKODA	FABIA, OCTAVIA, RAPID, ROOMSTER, SUPERB, YETI	Gasoline Diesel (DI) and Diesel before 2006
SSANG YONG	ACTYON, CHAIRMAN, KORANDO, KYRON, MUSSO, REXTON, RODIUS	Gasoline and Diesel
SUBARU	IMPREZA, FORESTER, LEGACY, TREZIA, TRIBECA, WRX	Diesel
SUZUKI	ALTO, CELERIO, WAGON, SPLASH, SWIFT, IGNIS, SX4, LIANA, KIZASHI, JIMNY, VITARA, GRAND VITARA	Gasoline and Diesel with particulate filters
UAZ	3151, HUNTER, PATRIOT, PICKUP, CARGO	Gasoline and Diesel
VOLKSWAGEN	AMAROCK, BORA, GOLF, JETTA, PASSAT, POLO, SHARAN, TIGUAN, TOUAREG, TOURAN	Gasoline Diesel (DI) and Diesel before 2006

* Third party data is used to determine the recommended products. Gazpromneft Lubricants accepts no liability for the suitability of any recommendation made. Any decisions you make based on this information are your sole responsibility. Before adding any products to your vehicle, please always check vehicle/equipment handbook to confirm the suitability of any product recommendations for your vehicle/equipment.

ISO 9001

ISO 14001

ISO/TS 16949

OHSAS 18001

CERTIFIED

GAZPROMNEFT – LUBRICANTS, LTD.
14/3, Krzhizhanovskogo Street, Moscow, 117218 Russia
Tel: +7 (495) 642-99-69
Fax: +7 (495) 921-48-63
www.gazpromneft-oil.com

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. The information contained is subject to change without notice. Gazpromneft-Lubricants accept no liability for any damage or loss resulting from using the product in purposes other than it intended, from any failure to comply with the recommendations or from hazards inherent in the nature of the material. If you require any further information please consult our technical helpdesk. E-mail: OilSupport@gazprom-neft.ru 05/2018



Gazpromneft Premium C3 5W-40

High Performance Passenger Vehicle Engine Oil



Engine oil



Synthetic



Multigrade



Gasoline and diesel engines



DPF Diesel Particulate Filters compatibility



Advanced polymers

Gazpromneft Premium C3 5W-40 is fully synthetic engine oil designed to provide long engine life through enhanced lubrication and protection of critical engine parts. It also provides enhanced protection for the latest emission control systems and turbochargers. Gazpromneft Premium C3 5W-40 can be used in modern GM, MB, BMW and VW Group gasoline and diesel engines.

Applications



- Turbo-charged and direct injection high performance engines
- Cars with environmental friendly exhaust systems, like EGR and TWC, DPF
- Passenger cars, SUV's, light trucks and vans

Features	Advantages and Potential Benefits
Broad vehicle application	High quality formulation suitable for a wide range of vehicles requiring premium quality product
Low ash additive package	Optimized for use with emission control systems like DPF (Diesel Particulate Filter) and TWC (Three Way Catalyst) to keep them in optimal conditions
Excellent low temperature performance	Instant oil flow at low temperatures provides easy cold starts and optimal lubrication from the first seconds after ignition
Wear protection	Strong oil film provides protection against wear under all operating conditions for long engine life
Deposit control	Prevents forming of sludge and harmful deposits through the use of advanced detergent additives for engine cleanliness

Meet the requirements:

- ACEA C3
- API SN (licensed)
- BMW Longlife-04
- Fiat 9.55535-S2
- Ford WSS-M2C917-A
- General Motors dexos2™
- MB 229.51
- Porsche A40

Approvals:

- VW 502.00
- VW 505.00
- VW 505.01

Typical Characteristics

Properties	Method	Gazpromneft Premium C3 5W-40
SAE Viscosity Grade	SAE J300	5W-40
Kinematic Viscosity @40°C, mm ² /s	ASTM D445	81,3
Kinematic Viscosity @100°C, mm ² /s	ASTM D445	14,1
Viscosity Index	ASTM D2270	180
Flash Point (COC), °C	ASTM D92	235
Pour Point, °C	ASTM D97	-36
Total Base Number, mg KOH/g	ASTM D2896	7,6
Density @15°C, kg/m ³	ASTM D4052	855
Sulfated Ash, wt%	ASTM D874	0,8

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.

Gazpromneft Premium C3 5W-40 recommendations*

Makes	Models	Engines
AUDI	A1, A3, A4, A5, A6, A7, A8, Q1, Q3, Q5, Q7	Gasoline Diesel before 2004
BMW	GT, Series1, Series3, Series5, Series7, X1,X3, X5, X6	Gasoline and Diesel
CADILLAC	BLS, ATS, CTS, XTS, XLR, ELR, STS, SRX, ESCALADE	Gasoline and Diesel
CHEVROLET	AVEO,CAPTIVA, CRUZE, EPICA, LACETTI, LANOS, NIVA, ORLANDO, REZZO, SPARK, VIVA	Gasoline and Diesel c 2007
CITROEN	C1, C2, C3, C4, C5, C6, C8, DS3, DS4, DS5	Gasoline (except THP, VTI, PureTech), Diesel before 2009
DACIA	SUPERNOVA, SOLENZA, SANDERO, LOGAN, DUSTER, LODGYM DOKKER	Diesel with particulate filters
DAEWOO	MATIZ, NEXIA, GENTRA	Gasoline
DAIHATSU	CUORE, MIRA, CHARADE, TREVIS, MOVE, SIRION, YOUNG RV, MATERIA, TERIOS, COPEN	Gasoline
DATSUN	MI-DO, ON-DO	Gasoline
DODGE	CALIBER, AVENGER	Diesel
FIAT	500, DOBLO, 600, SEICENTO, PANDA, PALIO, ALBEA, SIENA, IDEA, PUNTO, LINEA, BARCHETTA, BRAVO, STILO, MAREA, CROMA, SEDICI, QUBO, MULTIPLA, FREEMONT	Gasoline and Diesel before 2012
GAZ	3102, 31029, 3110, SIBER	Gasoline
GEELY	BEAUTY LEOPARD, BORUI, FREE CRUISER, EMGRAND, YUANJIN, VISION, GL EAGLE, HOAQING, LC PANDA, MEIRI ULIOU, KING KONG, JINGYING	Gasoline before 2014
GREAT WALL	HAVAL, FLORID, VOLEEX, COOLBEAR, HAVAL, TENGYI, HOVER	Gasoline
HONDA	JAZZ, CIVIC, FR-V, STREAM, ACCORD, LEGEND, HR-V, CR-V, NSX	Gasoline before 2004 , Diesel with particulate filters
HYUNDAI	ACCENT, ELANTRA, GETZ, I20, I30, I40 IX35, IX55, MATRIX, SANTA FE, SOLARIS, SONATA, TERRACAN, TUCSON, VERNA	Gasoline and Diesel before 2008 Diesel with particulate filters
INFINITI	G, I, JX, M, Q, EX, FX, QX	Gasoline
JEEP	GRAND CHEROKEE	Diesel
KIA	CARENS, CARNAVAL, CEED, CERATO, MAGENTIS/OPTIMA, PICANTO, RIO, SORENTO, SOUL, SPECTRA/SEPHIA/SHUMA, SPORTAGE, VENGA	Gasoline and Diesel before 2008 , Diesel with particulate filters
LADA	All models	Gasoline
MAZDA	2,3, 323, 5,6, ATENZA, AXELLA, CAPELLA, CX-3, CX-5, CX-7, CX-9, DEMIO, FAMILIA, PREMACY, VERISA	Diesel Skyactive
MERCEDES-BENZ	A, B, C, E, S, SLK, SLC, SL, CLA, CLC, CLK, CLS, CL, GLA, GLK, GLC, M, GLE, R, G, GL, GLS	Gasoline and Diesel
MITSUBISHI	AIRTREK, ASX, CARISMA, COLT, DION, GALANT, GRANDIS, L200, LANCER, CEDIA, LIBERO, MIRAGE, OUTLANDER, PAJERO, PININ, SPORT, SPACE STAR	Gasoline before 2009 Diesel with particulate filters
NISSAN	ALMERA, CUBE, EVALIA, JUKE, LEAF, MAXIMA QX, MICRA, MARCH, MURANO, NAVARA, NOTE, PATHFINDER, PATROL, TERRANO, PIXA, PULSAR, PRIMERA, QASHQAI, SKYLINE, TEANA, TIIDA, X-TRAIL	Gasoline and Diesel with particulate filters
PEUGEOT	206, 207, 3008, 307, 308, 406, 407, 408, 508	Gasoline (except THP, VTI, PureTech), Diesel before 2009
OPEL	ANTARA, ASTRA, CORSA, INSIGNIA, MERIVA, MOKKA, VECTRA, ZAFIRA	Gasoline and Diesel
SAAB	9-2, 9-3, 9-5, 9-7	Gasoline and Diesel
SEAT	MII, AROSA, IBIZA, LEON, CORDOBA, EXEO, TOLEDO, ALTEA, ALHAMBRA	Gasoline Diesel (DI) and Diesel before 2006
SKODA	FABIA, OCTAVIA, RAPID, ROOMSTER, SUPERB, YETI	Gasoline Diesel (DI) and Diesel before 2006
SSANG YONG	ACTYON, CHAIRMAN, KORANDO, KYRON, MUSSO, REXTON, RODIUS	Gasoline and Diesel
SUBARU	IMPREZA, FORESTER, LEGACY, TREZIA, TRIBECA, WRX	Diesel
SUZUKI	ALTO, CELERIO, WAGON, SPLASH, SWIFT, IGNIS, SX4, LIANA, KIZASHI, JIMNY, VITARA, GRAND VITARA	Gasoline and Diesel with particulate filters
UAZ	3151, HUNTER, PATRIOT, PICKUP, CARGO	Gasoline and Diesel
VOLKSWAGEN	AMAROCK, BORA, GOLF, JETTA, PASSAT, POLO, SHARAN, TIGUAN, TOUAREG, TOURAN	Gasoline Diesel (DI) and Diesel before 2006

* Third party data is used to determine the recommended products. Gazpromneft Lubricants accepts no liability for the suitability of any recommendation made. Any decisions you make based on this information are your sole responsibility. Before adding any products to your vehicle, please always check vehicle/equipment handbook to confirm the suitability of any product recommendations for your vehicle/equipment.

ISO 9001

ISO 14001

ISO/TS 16949

OHSAS 18001

CERTIFIED

GAZPROMNEFT – LUBRICANTS, LTD.
14/3, Krzhizhanovskogo Street, Moscow, 117218 Russia
Tel: +7 (495) 642-99-69
Fax: +7 (495) 921-48-63
www.gazpromneft-oil.com

While the information and figures given here are typical of current production and conform to specification, minor variations may occur. The information contained is subject to change without notice. Gazpromneft-Lubricants accept no liability for any damage or loss resulting from using the product in purposes other than it intended, from any failure to comply with the recommendations or from hazards inherent in the nature of the material. If you require any further information please consult our technical helpdesk. E-mail: OilSupport@gazprom-neft.ru 05/2018