



M-8G2k; M-10G2k ***Tractor diesel engine oils***

DESCRIPTION

Winter (M-8G2k) and summer (M-10G2k) motor oils exhibit perfect lubricating properties in bus and tractor diesel engines with or without low-pressure turbocharger. These oils are recommended for use also in stationary diesel and diesel generator engines. The products are blended with mineral base stocks and progressive additives that deliver improved performance compared to the similar G2 oils.

BENEFITS

- Superior resistance to lacquer and deposits formation ensures cleanness of engine components
- Carbon deposits prevention, protection from corrosion
- Good thermal stability and wear resistance

APPLICATIONS

- Car and tractor diesel engines with low-pressure turbocharger or/not, where oils of API CC or earlier specifications are required.
- High-speed stationary diesel and diesel generator engines.

SPECIFICATIONS AND APPROVALS

M-8G2k и M-10G2k oils comply with:

- API CC



TYPICAL PROPERTIES

<i>Typical Properties</i>	<i>M-8G2k</i>	<i>M-10G2k</i>
Viscosity, cSt @ 100 °C	8.2	11.3
Viscosity Index	98	95
Flash Point, COC, °C	236	241
Pour Point, °C	-34	-24
Base Number, mg KOH/g	7.0	7.0
Sulphated Ash, %	1.0	1.0
Density @ 20 °C, g/cm ³	0.884	0.890

HEALTH AND SAFETY

When used as directed, M-8G2k and M-10G2k oils have no adverse effects either on health or environment. Beyond normal hygiene no special precautions are required. Avoid contact with skin. Wear protective gloves. In case of contact, flush immediately with water and soap. For more information please refer to the Safety Data Sheet.

REDUCED ENVIRONMENTAL IMPACT

Place used product in an appropriate waste disposal container. Dispose via a licensed waste disposal contractor. Do not discharge waste lubricant into groundwater, watercourses, soil, sewerage or drainage systems.