

Gazpromneft ATF DX III

Automatic Transmission Fluid



Automatic Transmission Fluid



Semisynthetic



Power steering systems



Optimal friction performance



High wear protection



Oxidation stability

Gazpromneft ATF DX III is high quality automatic transmission fluid recommended for most passenger car and commercial automatic transmissions. It is designed to maximize transmission performance, reduce transmission wear, prevent leaks and maintain smooth shifting. Gazpromneft ATF DX III can be used in power steering systems and hydraulic applications where automatic transmission fluid is specified.

Applications



- Passenger and commercial automatic transmissions
- Power steering systems and hydraulic applications where automatic transmission fluid is specified

| Features | Advantages and Potential Benefits |
|---|---|
| Excellent thermal and oxidation stability | Reduced deposits and sludge build-up help provide outstanding transmission performance even under severe driving conditions |
| Good low temperature performance | Good fluidity at low temperatures providing good cold-start shifting |
| Good friction properties | Improved transmission efficiency and smooth shifting performance |
| Compatible with all common seal materials | Excellent leakage control |

Meet the requirements:

- General Motors DEXRON® IIIG
- General Motors TASA
- MB 236.1
- MB 236.11
- MB 236.2
- MB 236.3
- MB 236.5
- MB 236.6
- MB 236.7
- Allison C-4
- BMW LA 2634, LT 71141
- Caterpillar TO-2
- Ford MERCON
- MAN 339 Type V1/Z1
- Voith H55.6335
- Volvo 97341, CE 97340
- ZF TE-ML 02F, 03D, 04D, 05L, 09,11B, 14A, 17C, 21L

Typical Characteristics

| Properties | Method | Gazpromneft ATF DX III |
|--|------------|------------------------|
| Color | visually | red |
| Kinematic Viscosity @100°C, mm ² /s | ASTM D445 | 7,2 |
| Brookfield @-40°C, mPa·s | ASTM D2983 | 16000 |
| Flash Point (COC), °C | ASTM D92 | 213 |
| Pour Point, °C | ASTM D97 | -48 |
| Density @15°C, kg/m ³ | ASTM D4052 | 860 |

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.