

G-Special Hydraulic HVLPD-46

Detergent Hydraulic Oil

G-Special Hydraulic HVLPD-46 is high performance detergent based oils designed for hydraulic systems on stationary and mobile equipment that operate in climates where ambient temperatures can vary widely. It based on specially selected high viscosity index base oils and advanced ashless additive technology coupled with highly shear viscosity modifiers to provide reliable performance in applications where contamination by water is unavoidable.

Applications



- Hydraulic and fluid power transmission systems operating in wide variations of temperature and where water or contamination may enter the system
- Mobile hydraulic units (excavators, bulldozers, wheel loaders, trucks)
- Stationary hydraulic equipment operating outdoors

Features	Advantages and Potential Benefits
Excellent demulsibility	Preventing water accumulation, without deteriorating the good anticorrosion and lubrication properties
Special detergent/dispersant additive system	Excellent keep-clean performance in the hydraulic system
High viscosity index and good shear stability	Enhanced to help provide the required oil film to protect parts, over a long service life.
Ashless friction additives	Reduced wear for systems using various metallurgy for excellent performance of components. Providing non contaminated waste water for environmentally friendly disposal
Excellent corrosion protection	Preventing corrosion in the presence of water for increased equipment protection and equipment life
Good compatibility with seal materials	Reduced leakage, oil consumption and contamination entering helping to reduce maintenance, extend equipment reliability and higher productivity

Meets the requirements:

- DIN 51524 Part 3 (except demulsifying ability)

Typical Characteristics

Properties	G-Special Hydraulic HVLPD-46	Method
ISO Viscosity Grade	46	
Kinematic Viscosity @ 40°C, mm ² /s @ 100°C, mm ² /s	46 8,6	ASTM D 445
Viscosity Index	155	ASTM D 2270
Flash Point (COC), °C	220	ASTM D 92
Pour Point, °C	-45	ASTM D 97
Cleanliness class, max	-/17/14 (-/15/13*)	ISO 4406
Density @20°C, kg/m ³	890	ASTM D 4052
Copper Strip Corrosion, 3 hrs @ 100°C	1B	ASTM D 130

* - available upon request

Health, Safety & Environment

Information is provided for products in the relevant Safety Data Sheet (SDS). This provides guidance on potential hazards, precautions and first-aid measures, together with environmental effects and disposal of used products. SDS's are available upon request through your sales contract office. This product should not be used for purposes other than its intended use.

✔ ISO 9001

✔ ISO 14001

✔ ISO/TS 16949

✔ OHSAS 18001

CERTIFIED